





















































Network Camera - NVR

Items	Description	User Price
Lite Mini Bullet Series		
DS-2CV1021G0-IDW1	 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP66 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in WIFI	call
DS-2CD1021G0E-I	 Hikvision 2MP Mini IR Network Bullet camera, 1/2.8" Progressive CMOS, ICR, 1920x1080:20fps (P)/N, H.265 / H.264+ & H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE Rs. 0.001Is our price higher or showing zero? Please chat now and ask for the best price. Prices if shown are inclusive of applicable taxes. Tax rate may be adjusted as per customer's taxation status. For supply of product only, excluding any cabling and/or installation. Shipping charges can sometimes vary.	IRR 13,932,000
DS-2CD1023G0E-I	 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 28,900,000
DS-2CD1023G0-I	 2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)	IRR 23,500,000
DS-2CD1023G0-IUF	 2.0 MP IR Network Bullet Camera -1/2.7" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8-4 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range)- Built-in microphone	IRR 40,770,000
DS-2CD1043G0E-I	 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range) - ECO CASE	call
DS-2CD1047G0-L ColorVu Lite	 4 MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 4 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 48,590,000
DS-2CD1057G0-L	 5 MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 5 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 58,820,000
DS-2CD1043G0-I	 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 42,310,000
DS-2CD1053G0-I	 5.0 MP IR Network Bullet Camera, 1/2.7" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1920@20fps - Up to 30 m IR range, 2.8 mm/4 mm fixed lens - PoE (Power over Ethernet), H.265+, IP67, Dual stream, BLC, WDR 120 dB(Wide Dynamic Range)	IRR 31,370,000
Lite Dome Series		
DS-2CD1323G0E-I	 1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 29,590,000
DS-2CD1323G0-IU	 1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone	IRR 20,990,000
DS-2CD1323G0-IUF	 2 MP Fixed Turret Network Camera 1/2.7" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm fixed lens - H.265+ - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - Built-in microphone. Metal & Plastic	IRR 27,110,000
DS-2CD1327G0-L ColorVu Lite	 2 MP ColorVu Lite Fixed Turret Network Camera. High quality imaging with 2 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 32,160,000
DS-2CD1347G0-L ColorVu Lite	 4 MP ColorVu Lite Fixed Turret Network Camera. High quality imaging with 4 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 72,230,000
DS-2CD1357G0-L	 5 MP ColorVu Lite Fixed Turret Network Camera. High quality imaging with 5 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 58,790,000





















DS-2CD2327G2-L		2 MP ColorVu Fixed Turret Network Camera High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Focusing on human and vehicle classification Built-in microphone for real-time audio security (-U) 24/7 colorful imaging Water and dust resistant (IP67)	IRR 81,110,000
DS-2CD2347G2-L (2.8mm)		High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Built-in microphone for real-time audio security (-U) Focus on human and vehicle targets classification 24/7 colorful imaging Water and dust resistant (IP67)	IRR 78,910,000
DS-2CD2347G2-LU		4 MP ColorVu Fixed Turret Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Built-in microphone for real-time audio security (-U) Focus on human and vehicle targets classification 24/7 colorful imaging, Water and dust resistant (IP67)	IRR 89,760,000
DS-2CD1353G0-I		5 MP IR Fixed Network Turret Camera * 1/2.7" Progressive Scan CMOS, * 2560 x 1920 @ 15fps * Color: 0.01 Lux @ (F1.2; AGC ON), 0.028 Lux @ (F2.0; AGC ON), * 2.8/4/6 mm fixed lens * H.265+, H.265, H.264+, H.264 * 3D Digital Noise Reduction based on deep learning * IP67	IRR 52,050,000
DS-2CD2743G2-IZS		4 MP AcuSense Motorized Varifocal Dome Network Camera High quality imaging with 4 MP resolution Motorized varifocal lens for easy installation and monitoring Clear imaging against strong back light due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification 24/7 colorful imaging	IRR 132,760,000
DS-2CD1123G0E-I		2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3 (Digital Noise Reduction) 1920 x 1080@30fps - 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens, PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 IP67, IK10 Digital WDR (Wide Dynamic Range) ECO CASE	IRR 26,470,000
DS-2CD1123G0-I		2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS - 3 (Digital Noise Reduction) 1920 x 1080@30fps - 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens, PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 IP67, IK10 Digital WDR (Wide Dynamic Range)	call
DS-2CD2126G2-ISU 2.8mm		2 MP AcuSense Fixed Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Focus on human and vehicle classification 24/7 colorful imaging -SU: Built-in microphone for real-time audio security, Audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 81,540,000
DS-2CD1143G0-I		4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3dB tru (Digital Noise Reduction), 2560 x 1440@20fps - 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens, PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 IP67, IK10 Dual stream, Digital WDR (Wide Dynamic Range)	IRR 47,460,000
DS-2CD1143G0-IUF		High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range -UF: Built-in microphone for real-time audio security	IRR 49,520,000
DS-2CD1153G0-I		5 MP Fixed Dome Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) and vandal resistant (IK10) EXIR 2.0: advanced infrared technology with long IR range	IRR 54,540,000
DS-2CD1743G0-IZ		4 MP Varifocal Dome Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR 256 memory slot for storage 2.8-12 mm motorized varifocal lens for easy installation and monitoring Water and dust resistant (IP67) and vandal resistant (IK10) EXIR 2.0: advanced infrared technology with long IR range	IRR 91,340,000
DS-2CD1353G0-I 2.8mm		5MP Fixed Turret Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range -UF: Built-in microphone for real-time audio security	IRR 35,530,000
Mini Bullet Series			
DS-2CD2025FWD-I		2 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB WDR technology, Water and dust resistant (IP67), Robust structure design with full metal material.	IRR 42,050,000
DS-2CD2021G1-I		2 MP IR Fixed Network Bullet Camera High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Water and dust resistant (IP67) Support up to 256 GB SD card storage	IRR 49,980,000
DS-2CD2023G0-I		2 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 1920 x 1080@30fps - 2.8/4/6 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON) 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 - Built-in IR LED SD/SDHC/SDXC card slot, up to 128 GB	IRR 37,740,000

DS-2CD2023G2-I		2 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.265+ - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67-Up to 40 m IR range - Built-in micro SD/SDHC/SDXC card slot, u 256 GB	IRR 42,810,000
DS-2CD2027G2-L ColorVu Lite		2 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.265+ - 120dB WDR - BLC/3D DNR/ROI - IP67-Up to 40 m IR range - Built-in micro SD/SDHC/SDXC card slot, u 256 GB	IRR 71,040,000
DS-2CD2043G0-I		4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 Built-in micro SD/SDHC/SDXC card slot, u 128 GB	IRR 53,920,000
DS-2CD2043G2-I		4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 Built-in micro SD/SDHC/SDXC card slot, u 256 GB	IRR 66,460,000
DS-2CD2043G2-IU		4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 DR technology Efficient H.265+ compression technology -U: Built-in microphone for real-time audio security Water and dust resistant (IP67)	IRR 69,980,000
DS-2CD2043G0-I (Black)		4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS - 2560 × 1440@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 Built-in micro SD/SDHC/SDXC card slot, u 128 GB	call
DS-2CD2047G2-L ColorVu Lite		4 MP IR Fixed Bullet Network Camera - 1/1.8" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265, H.265+ - 130dB WDR - BLC/3D DNR/ROI - IP67-Up to 40 m IR range - Built-in micro SD/SDHC/SDXC card slot, u 256 GB	IRR 68,760,000
DS-2CD2063G0-I		6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2848@20fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 Built-in micro SD/SDHC/SDXC card slot, u 128 GB	IRR 41,620,000
DS-2CD2063G2-I		6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 Built-in micro SD/SDHC/SDXC card slot, u 128 GB	IRR 64,400,000
DS-2CD2063G2-I (2.8mm)		6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 Built-in micro SD/SDHC/SDXC card slot, u 128 GB	IRR 46,070,000
DS-2CD2043G2-I		6 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 3072 × 2048@20fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 Built-in micro SD/SDHC/SDXC card slot, u 256 GB	IRR 41,620,000
DS-2CD2045FWD-I		4 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 DR technology Water and dust resistant (IP67)	IRR 44,380,000
DS-2CD2083G0-I		8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 × 2160@15fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 Built-in micro SD/SDHC/SDXC card slot, u 128 GB	IRR 45,110,000
DS-2CD2083G2-I		8 MP IR Fixed Bullet Network Camera - 1/2.8" Progressive Scan CMOS - 3840 × 2160@15fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 Built-in micro SD/SDHC/SDXC card slot, u 256 GB	IRR 54,810,000
DS-2CD2087G2-LU ColorVu Lite		8 MP IR Fixed Bullet Network Camera - 1/1.2" Progressive Scan CMOS - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 130dB WDR - BLC/3D DNR/ROI/HLC - IP67 Built-in micro SD/SDHC/SDXC card slot, u 256 GB, Built-in microphone	IRR 156,550,000
Dome Series OS			
DS-2CD2123G0-IS		2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 IK10 Built-in micro SD/SDHC/SDXC card slot, u 128GB S: Audio/Alarm IO connectors	call
DS-2CD2123G2-I		2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS - 1920 × 1080@30fps - 2.8/4mm-fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR - H.265 - Three streams - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI/HLC - IP67 IK10 Built-in micro SD/SDHC/SDXC card slot, u 256GB S: Audio/Alarm IO connectors, 30 m IR range	IRR 41,920,000
DS-2CD2125FHWD-IS		2 MP High Frame Rate Fixed Dome Network Camera, High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 DR technology WDR technology High frame rate video to illustrate smooth movement, S: audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10), Robust structure design with full metal materials.	IRR 49,060,000
DS-2CD2H25FWD-I2S		2 MP Powered-by-DarkFighter varifocal turret Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 DR technology Water and dust resistant (IP66) and vandal resistant (IK10) Motorized varifocal lens for easy installation and monitoring Robust structure design with full metal materials.	IRR 138,870,000
DS-2CD2143G2-IU		4 MP Vandal Built-in Mic Fixed Dome Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 DR technology Efficient H.265+ compression technology, Built-in microphone for real-time audio security proof Water and dust resistant (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification learning	IRR 52,710,000



















e to dB W



DS-2CD2143G0-IS (Black)		4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 × 1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	call
DS-2CD2143G0-IU		4 MP IR Fixed Dome Network Camera - 1/3" Progressive Scan CMOS, 2688 × 1520@30fps, 2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - Three streams -120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP66- IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	call
DS-2CD2145FWD-IS		4 MP Powered-by-DarkFighter Fixed Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology -S: audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 49,060,000
DS-2CD2146G2-I		4 MP AcuSense Fixed Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification proof earning Built-in microphone for real-time audio security (-SU) Water and dust resistant (IP67) and vandal-resistant (IK10)	IRR 49,240,000
DS-2CD2147G2-LSU (2.8mm)		4 MP ColorVu Fixed Dome Network Camera, High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 130 DR technology 24/7 colorful imaging based on deep learning Focus on human and vehicle targets classification earning -SU: Built-in microphone for real-time audio security, audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 57,200,000
DS-2CD2163G0-IS		6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3672 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	call
DS-2CD2163G0-IS (Black)		6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	IRR 43,680,000
DS-2CD2163G0-IU		6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP66 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - S: Audio/Alarm IO connectors	IRR 44,600,000
DS-2CD2163G2-IU (2.8mm)		6 MP AcuSense Vandal Fixed Dome Network Camera High quality imaging with 6 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification proof earning Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal-resistant (IK10)	IRR 62,620,000
DS-2CD2166G2-I (2.8mm)		6 MP AcuSense Fixed Dome Network Camera High quality imaging with 6 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology based on deep learning Clear imaging against strong back light due to 120 dB WDR technology Focus on human and vehicle targets classification earning Built-in microphone for real-time audio security (-SU)	IRR 53,050,000
DS-2CD2183G0-IS		8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors based on deep learning	IRR 48,790,000
DS-2CD2183G0-IU		8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP66, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - Built-in microphone	call
DS-2CD2183G2-IU		8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB - 1/2.8" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265 - 2 Behavior analyses and face detection -120dB WDR - Built-in microphone, GB	IRR 65,710,000
DS-2CD2183G0-IS (Black)		8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 47,840,000
DS-2CD2185FWD-IS		4K Fixed Dome Network Camera High quality imaging with 8 MP resolution, Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology -S: audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10) Robust structure design with full metal materials.	IRR 65,070,000
DS-2CD2186G2-I (2.8mm)		4K AcuSense Fixed Dome Network Camera, High quality imaging with 8 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Focus on human and vehicle targets classification earning Built-in microphone for real-time audio security (-SU) Audio and alarm interface available(-SU) Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 65,930,000
DS-2CD2143G2-2I (2.8mm)		1/3" Progressive Scan CMOS, 2688 × 1520@30fps, 2.8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, Three streams, 120dB WDR, Focus on human and vehicle targets classification based on deep learning, BLC/3D DNR/ROI - IP67 Built-in micro SD/SDHC/SDXC card slot, up to 256 GB - u 60m IR range	IRR 76,140,000
DS-2CD2143G2-2I (4mm)		1/3" Progressive Scan CMOS, 2688 × 1520@30fps, 2.8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, Three streams, 120dB WDR, Focus on human and vehicle targets classification based on deep learning, BLC/3D DNR/ROI - IP67 Built-in micro SD/SDHC/SDXC card slot, up to 256 GB - u 60m IR range	IRR 67,350,000



















DS-2CD2T43G2-4I(4mm)		1/3" Progressive Scan CMOS,2688 ×1520@30fps-4mm fixed lens - Color: 0.01 Lux @(F1.2, AGC ON), 0.018 Lux @(F1.6, AGC ON), 0 Lux with IR, H.265+, Three streams, 120dB WDR, Focus on human and vehicle targets classification based on deep learning, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 256 GB-up to 80m IR range	IRR 69,670,000
DS-2CD2T43G0-15		1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @(F1.2, AGC ON), 0.018 Lux @(F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 46,400,000
DS-2CD2T43G0-18		1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @(F1.2, AGC ON), 0.018 Lux @(F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 80m IR range	IRR 48,100,000
DS-2CD2T45FWD-15		4 MP Powered-by-DarkFighter Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67)	IRR 52,170,000
DS-2CD2T45FWD-18		4 MP Powered-by-DarkFighter Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67)	IRR 54,510,000
DS-2CD2T46G2-4I(2.8mm)		4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning	IRR 57,190,000
DS-2CD2T46G2-ISU/SL2.8mm		4 MP AcuSense Strobe Light and Audible Warning Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Active strobe light and audio alarm to warn intruders off Provides real-time security via built-in two-way audio Water and dust resistant (IP67)	IRR 60,360,000
DS-2CD2T47G2-L		4 MP ColorVu Fixed Bullet Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)	IRR 57,980,000
DS-2CD2T63G0-15		6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR	call
DS-2CD2T63G0-18		6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range	IRR 52,700,000
DS-2CD2T63G2-4I		High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning Water and dust resistant (IP67)	IRR 80,860,000
DS-2CD2T66G2-2I		6 MP AcuSense Fixed Bullet Network Camera High quality imaging with 6 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning	IRR 58,980,000
DS-2CD2T66G2-4I		6 MP AcuSense Fixed Bullet Network Camera High quality imaging with 6 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning	IRR 78,940,000
DS-2CD2T87G2-1K		4 K ColorVu Fixed Bullet Network Camera • High quality imaging with 8 MP resolution • Efficient H.265+ compression technology • Clear imaging against strong back light due to 130 dB WDR technology • Focus on human and vehicle classification based on deep learning • 24/7 colorful imaging	IRR 113,860,000
DS-2CD2T83G0-15		8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G	call
DS-2CD2T83G0-18		8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 55,760,000
DS-2CD2883G2-I2S		8 MP AcuSense Motorized Varifocal Bullet Network Camera High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP67) and vandal-resistant (IK10)	IRR 90,690,000
DS-2CD2T83G2-4I		High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning Water and dust resistant (IP67)	IRR 93,900,000
DS-2CD2T88G2-4I(2.8mm)		4K AcuSense Fixed Bullet Network Camera High quality imaging with 8 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light by 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning	IRR 107,470,000
DS-2CD2T86G2-4I(4mm)		4K AcuSense Fixed Bullet Network Camera High quality imaging with 8 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light by 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)	IRR 100,420,000




































DS-2CD2327WD-I		2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264 High performance EXI - 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	IRR 35,500,000
DS-2CD2345FWD-I		4MP Powered by DarkFighter Fixed Turret Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology Water and dust resistant (IP67)	IRR 45,950,000
DS-2CD2523G0-IS		1/2.7" Progressive Scan CMOS - 1920 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: u 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, u 128 - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR - S: Built-in MIC, audio/alarm IO	call
DS-2CD2525FWD-I		2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera, High quality imaging with 2MP resolution Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology, -W: Wi-Fi connection -S: built-in microphone, audio and alarm interface available Water and dust resistant (IP66) and vandal (IK08), Mini size suitable for limited space	IRR 49,840,000
DS-2CD2542FWD-IS		1/3" Progressive CMOS, 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @ (F1.6, AGC ON), 0 lux with IR - 2688 1520@20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: u 10m, support on-board storage u 128GB(SD card not included), Hik-Connect, audio service-S: Built-in MIC, audio/alarm IO	call
DS-2CD2543G0-IS		1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @ (F1.6, AGC ON), 0 lux with IR - 2688 1520@30fps - IR: u 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, u 128 - PoE - EXIR - S: Built-in MIC, P audio/alarm IO	call
DS-2CD2563G0-IS		1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @ (F1.6, AGC ON), 0 lux with IR - 3072 * 2048@20fps - IR: u P to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, u P to 128 GB - PoE - EXIR - S: Built-in MIC, audio/alarm IO	call
DS-2CD1623G0-I		2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 * 1080@30fps - 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264 Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, u 128 GB	IRR 43,180,000
DS-2CD1623G0-JZ		2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 * 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264 Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, u 128 GB - Motorized VF lens	call
DS-2CD1643G0-I		4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI 2560 1440@20fps - Up to 30 m IR range - 2.8 mm 12 mm varifocal lens - IP67 - H.265+, H.265, H.264+, H.264 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) Built-in micro SD/SDHC/SDXC card slot, u 128 GB	call
DS-2CD1643G0-JZ		4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI 2560 * 1440@20fps - Up to 30 m IR range - 2.8 mm 12 mm varifocal lens - IP67 - H.265+, H.265, H.264+, H.264 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) Built-in micro SD/SDHC/SDXC card slot, u 128 GB - Motorized VF lens	IRR 81,350,000
DS-2CD1653G0-I		1/3" progressive scan CMOS - BLC/3D DNR/ROI 2560 1440@20fps - 30 m IR range, 2.8 mm 12 mm varifocal lens - IP67 - H.265+, H.265, H.264+, H.264 120 dB WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) Built-in micro SD/SDHC/SDXC card slot, u 128 GB	IRR 52,250,000
DS-2CD1723G0-I		2 MP VF Dome Network camera - 1/2.8" progressive scan CMOS - 3 (Digital Noise Reduction) 1920 1080@30fps - 30 m IR range - 2.8 mm 12 mm manual vari-focal lens - PoE (Power over Ethernet) IP67, IK10 H.265+, H.265, H.264+, H.264 Dual stream - Digital WDR	call
DS-2CD1743G0-I		4 MP VF Network Dome Camera, 1/3" progressive scan CMOS - 3 (Digital Noise Reduction), 2560 1440@20fps * 30 m IR range, 2.8 mm 12 mm manual/motorized (with - PoE (Power over Ethernet) IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB WDR	IRR 28,160,000
DS-2CD1743G0-JZ		4.0 MP VF Network Dome Camera-1/3" progressive scan CMOS - 3 (Digital Noise Reduction) Up to 2560 1440@20fps - 30 m IR range, 2.8 mm 12 mm manual/motorized (with - PoE (Power over Ethernet) IP67 H.265+, H.265, H.264+, H.264 - Dual stream - 120 dB WDR - Motorized VF lens	IRR 80,800,000
DS-2CD1753G0-JZ		5 MP Varifocal Dome Network Camera High quality imaging with 5 MP resolution, Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR, 256 memory card slot for storage, 2.8 12 mm motorized varifocal lens for easy installation and monitoring, Water and dust resistant (IP67) and vandal (IK10), EXIR 2.0: advanced infrared technology with long IR range	IRR 98,470,000
DS-2CD1753G0-I		5 MP Varifocal Dome Network Camera High quality imaging with 5 MP resolution, Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR, Up to 256 GB memory card slot for storage, 2.8 to 12 mm motorized varifocal lens for easy installation and monitoring, Water and dust resistant (IP67) and vandal proof (IK10), EXIR 2.0: advanced infrared technology with long IR range	IRR 54,860,000
DS-2CD2625FWD-IZS		2MP Powered by DarkFighter Varifocal Bullet Network camera High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology, Clear imaging against strong back light due to 120 dB WDR technology, Water and dust resistant (IP66) and vandal (IK10), Motorized varifocal lens for easy installation and monitoring full metal materials.	IRR 110,210,000



















to dB tu

proof

DS-2CD2632F-I		3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536/25fps(P)/30fps(N), 2.8~12mm lens, H.264/MJPEG/H.264+ , dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: u 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 60,500,000
DS-2CD2643G2-IZS		4 MP WDR Motorized Varifocal Bullet Network Camera, High quality imaging with 4 MP resolution Motorized varifocal lens for easy installation and monitoring Clear imaging against strong backlight due to 120 e WDR technology Efficient H.265+ compression technology, (IP67) and vandal resistant (IK10) Focus on human and vehicle targets classification earning	IRR 110,320,000
DS-2CD2645FWD-IZS		4 MP Powered-by-DarkFighter Varifocal Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 e WDR technology Water and dust resistant (IP66) and vandal (IK10)	IRR 92,660,000
DS-2CD2663FG0-IZS		6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, u 128 GB - 1/2.9" Progressive Scan CMOS - 3072 2048@20 -2.8 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 IR Range u 50m - 120dB WDR - 2 Behavior analyses, and face detection - Z:Motorized VF lens	call
DS-2CD2683G2-IZS		8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x2160@15fps - 2.8 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 IR Range u 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - P67, IK10 Z:Motorized VF lens	IRR 90,690,000
DS-2CD2685FWD-IZS		1/2.5" Progressive Scan CMOS 3840 2160 resolution H.265, H.265+ 120dB WDR IP67, IK10 BLC/3D DNR/ROI Smart encoding: Support low bit rate, low latency 4 behavior analyses and face detection	IRR 124,080,000
DS-2CD2686G2-IZS		4K AcuSense Varifocal Bullet Network Camera, High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 e WDR technology Focus on human and vehicle targets classification earning Audio and alarm interface available Water and dust resistant (IP66) and vandal (IK10)	IRR 118,340,000
DS-2CD2743G2-IZS		4 MP Outdoor WDR Motorized Varifocal Dome Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 e WDR technology-S: audio and alarm interface available-Water and dust resistant (IP67) and vandal (IK10)-Motorized varifocal lens for easy installation and monitoring-Robust structure design with full metal materials	IRR 100,080,000
DS-2CD2745FWD-IZS		4 MP Powered-by-DarkFighter Varifocal Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 e WDR technology Water and dust resistant (IP66) and vandal (IK10) Motorized varifocal lens for easy installation and monitoring Robust structure design with full metal materials	IRR 92,660,000
DS-2CD2746G2-IZS		4 MP Powered-by-DarkFighter Varifocal Dome Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 e WDR technology, Efficient H.265+ compression technology False alarm reduction through human and vehicle target classification earning, -S: audio and alarm interface available Water and dust resistant (IP66) and vandal resistant (IK10)	IRR 152,400,000
DS-2CD2763G0-IZS		6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072x2048@20fps - 2.8 12 mm varifocal lens - Max IR distance: 30 m - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, u 128 - Z: based on deep learning, Motorized VF lens	call
DS-2CD2763G1-IZS		High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 e WDR technology -S: audio and alarm interface available Water and dust resistant (IP67) and vandal (IK10) Motorized vari-focal lens for easy installation and monitoring	IRR 142,160,000
DS-2CD2783G2-IZS		8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 x2160@15fps - Max IR distance: 30 meters - 2.8 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67 IK10 Built-in micro SD/SDHC/SDXC card slot, u 128 - Z: based on deep learning, Motorized VF lens	IRR 120,000,000
DS-2CD2786G2-IZS		4K AcuSense Varifocal Dome Network Camera, High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 e WDR technology Focus on human and vehicle targets classification earning Audio and alarm interface available, Water and dust resistant (IP66) and vandal (IK10)	IRR 195,970,000
DS-2CD2955FWD-I		5 MP Network Fisheye Camera, 5 megapixel high resolution, 2560 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal 180°, vertical 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, u 128 GB, 8m IR range	IRR 126,380,000
DS-2CD2955FWD-IS		5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 x 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal 180°, vertical 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, u 128 GB, 8m IR range, -S: Audio/Alarm IO	IRR 100,450,000
DS-2CD6332FWD-IS		FOV Up to FOV 1/3" Progressive Scan CMOS Max. 2048 1536 @30fps p to 15 live view display modes, 120dB WDR 15m IR range, Built-in microphone and speaker 2 behavior analyses, 1 statistic	IRR 178,300,000
IDS-2CD6412FWD/C		Up to 1.3MP, 2.1mm 115degree Fixed Lens 1/3" CMOS 30 1280 x 960, People Counting, WDR 120dB, 3D DNR Electronic Day/Night, H.264, MJPEG, MPEG4, Alarm IO ONVIF, PSIA, CGI, ISAPI, Support real-time people entering/exiting data. Support statistical traffic report based on configurable time interval (day/week/month/year), Support Smart Codec, high bandwidth efficiency, low time delay and optimized bit rate, Support on-board storage, Micro SD/SDHC/SDXC u 128GB, card not included, Defog, Electronic Image Stabilization, various BLC modes Support Smart Detection, including: Intrusion Detection, Audio Exception Detection, etc. Main unit: 107.6mm x 78mm x 33.5mm Lens: 48.7mm x 30.7mm x 31.5mm	IRR 224,880,000

DS-2CD2420F-IW		2 megapixel (1920 x 1080 @30fps) resolution - Standard video compression with high compression ratio, ROI (region of interest) encoding - Progressive scan CMOS - Built-in Micro SD/SDHC/SDXC card slot - 128 GB - IR range approx. 10 meters Two-way audio - Built-in microphone and speaker - Support Wi-Fi, Support WPS configuration with one touch - Support PIR (Passive Infrared Detection) - IR cut filter with auto switch - Integrated mount for easy installation, Digital Wide Dynamic Range, Auto-electronic shutter	call
DS-2CD2421G0-IW		Up to 2.0MP Progressive Scan CMOS - 1920 x 1080@30fps - IR: 10m - PIR: 10m - H.265, H.265+ DWDR - Built-in Micro SD/SDHC/SDXC slot, - 128 GB - PoE - EXIR - Wi-Fi (Optional) Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	IRR 28,480,000
DS-2CD2423G0-IW		1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - IR: 10m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	call
DS-2CD2443G0-IW		1/3" Progressive Scan CMOS - 2688 x 1520@30fps - IR: 10m - PIR: 10m - 120dB WDR - Video Compression: H.265+/H.265/H.264+H.264 MJPEG/Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° - W: Built-in Wi-Fi with WPS	IRR 39,375,000
DS-2CD2D14WD		1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	call
DS-2CD2Q10FD-IW		1 MP CMOS PT Cam - 1/4" Progressive Scan CMOS - 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3 IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% Pan & Tilt Control Pan: 0°-355°, Tilt: -20°-90	IRR 31,300,000
DS-2CV2U21FD-IW		2.0 MP Network Cube Cam - 1/2.8" Progressive Scan CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Built-in microphone and speaker, support two-way audio, Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.	IRR 21,790,000
DS-2DE4A225IW-DE		4-inch 2 MP 25X Powered by DarkFighter IR Network High quality imaging with 2 MP resolution. Excellent low-light performance via powered-by, DarkFighter technology. Clear imaging against strong back lighting due to 120 DR technology, Pan and tilt ability enables camera to monitor zones of interest. 25x optical zoom allows for closer viewing of subjects in expansive areas. 50m IR range ensures safety at night (IP66)	IRR 124,900,000
DS-2DE4A320IW-DE		1/2.8" Progressive Scan CMOS - 2048 x 1536 Resolution - 20x Optical Zoom, 16x Digital Zoom - DR, 3D DNR, HLC, Smart IR + Basic Smart Suite Analysis - 120dB WDR - 50m IR Distance + H.265+ Video Compression Supported + IP66 Protection 12 VDC & PoE+ (802.3at, Class 4)	IRR 274,170,000
DS-2DE4220IW-DE		2MP 20x Network IR Speed Dome - 1/2.8" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W: 0.002lux/F1.5, Optical Zoom: 20x, Focus: 4.7-94.0mm, Digital Zoom: 16X, Pan range: 360° endless; Tilt range: -15°-90° (Auto Flip), Pan Speed: 0.1°/s, Tilt Speed: 0.1°/s, 80°/s, 100m IR Distance, POE & 12VDC	call
DS-2DE4225IW-DE-S6		4-inch 2 MP 25X Powered by DarkFighter IR Network 1/2.8" progressive scan CMOS, High quality imaging with 2 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology 25x optical zoom and 16x digital zoom provide close up views over expansive areas WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus Expansive night view with up to 100 m IR distance Support H.265+/H.265 video compression - powered-by-DarkFighter technology	IRR 222,510,000
DS-2DE4225IW-DE-T5		2MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOS - 1920 x 1080@30fps resolution - Min. Illumination: Color: 0.005 Lux @ (F1.6, AGC ON) B/W: 0.001 Lux @ (F1.6, AGC ON) Lux with IR 25x optical zoom Focal Length 4.8 mm - 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	IRR 210,020,000
DS-2DE4425IW-DE-T5		4MP 25x Network IR Speed Dome - 1/2.8" progressive scan CMOS - Up to 2560 x 1440@30fps resolution - Min. Illumination: Color: 0.005 Lux @ (F1.6, AGC ON) B/W: 0.001 Lux @ (F1.6, AGC ON) Lux with IR 25x optical zoom Focal Length 4.8 mm to 120 mm - 16x digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with powered-by-DarkFighter technology	IRR 223,060,000
DS-2DF823615W-AELW		Optical Defog 2MP (1920*1080) Full HD 36X Optical Zoom Ultra-low illumination, 120db True WDR Smart Tracking, Smart Detection EIS (Electronic Image Stabilization) 500m IR distance Optional wiper(-W)	IRR 1,143,020,000
DS-2DE5220IW-AE		2.54cm (1/2.8") Progressive Scan CMOS 1920 x 1080 resolution 20x Optical Zoom, 16x Digital Zoom, Digital WDR 3D intelligent positioning function, 150 m IR distance Hi-PoE/24 VAC power supply, Support H.265 video compression	IRR 338,660,000
DS-2DE5432IW-AE-S5		1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology 32x optical zoom, 16x digital zoom WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus 150 m IR distance Accurate human and vehicle target classification, alarm, and linked tracking based on learning algorithm, Face capture: 5 red at the same time	IRR 229,040,000

DS-2DE5230W-AE		2MP 30× Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	call
DS-2DF5276-AEL		1/3" progressive Scan CMOS 30x / 20x optical Zoom, 16x digital Zoom Smart tracking, eis, defog True day/Night, D wdr, 3D DNR 3D Intelligent positioning, Connectivity Technology: Wireless	IRR 447,450,000
DS-2DF5276-AE3		1/3" Progressive Scan CMOS 30X optical zoom, 16X digital zoom, ONVIF Smart Tracking, EIS, Defog, True Day/Night, D WDR, 3D DNR 3D intelligent positioning, Triple stream 24VAC / High-PoE power supply, Outdoor / Indoor	IRR 562,530,000
DS-2DF6A236X-AEL		6-inch 2 MP 36X DarkFighter Network High quality imaging with 2 MP resolution Excellent low-light performance via DarkFighter technology 36x optical zoom provides close up views over expansive areas Intelligent functions based on learning Water and dust resistant (IP67) and vandal (IK10).	IRR 520,800,000
DS-2CDE5432IW-AE		5-inch 4 MP 32X Powered by DarkFighter Network 1/2.8" Progressive Scan CMOS High quality imaging with 4 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Accurate human and vehicle target classification, alarm, and linked tracking based on learning algorithm	IRR 229,050,000
DS-2CD5220IW-AE		2MP 20X Network IR Speed Dome, 1920 1080@60fps resolution, Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON), B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR, 32× optical zoom, 16× digital zoom, WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus, 150 m IR distance, 24 VAC & Hi-PoE, Support H.265+/H.265 video compression	IRR 231,170,000
DS-2DE7232IW-AE		2MP 32× Network IR Speed Dome, 1920 1080@60fps resolution, Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON), B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR, 32× optical zoom, 16× digital zoom, WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus, 150 m IR distance, 24 VAC & Hi-PoE, Support H.265+/H.265 video compression	call
DS-7600NI-E1/A		Advertising files import and preview, The output resolution is up to 1080P Third party network cameras supported, 8-ch synchronous playback 720P resolution, Up to 8 network cameras can be connected, Smart search and smart playback 1TB HDD WD10JUCT pre-installed	IRR 164,300,000
DS-7104NI-Q1/M		IP video input : 4-ch 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 40 Mbps - HDMI output : 1920 1080p/60Hz - Capacity : 1 SATA in 6TB capacity	IRR 26,860,000
DS-7104NI-Q1		4-ch Mini 1U NVR H.265+/H.265/H.264+/H.264 video compression Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth 4-ch network camera support Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output	IRR 20,290,000
DS-7104NI-Q1/4P/M		IP video input : 4-ch / 4-ch 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 40 Mbps - HDMI output : 1920 1080p/60Hz - Capacity : 1 SATA in 6TB capacity	call
DS-7604NI-Q1		IP video input : 4-ch 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 2160)/30Hz - Capacity : 1 SATA in 6TB capacity	call
DS-7604NI-Q1/4P		IP video input : 4-ch 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 2160)/30Hz - Capacity : 1 SATA in 6TB capacity	call
DS-7604NI-K1		IP video input : 4-ch 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 2160)/30Hz - Capacity : 1 SATA in 6TB capacity	IRR 61,560,000
DS-7604NI-K1/4P		IP video input : 4-ch 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 2160)/30Hz - Capacity : 1 SATA in 6TB capacity	IRR 82,740,000
DS-7108NI-Q1/M		IP video input : 8-ch 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 60 Mbps - HDMI output : 1920 1080p/60Hz - Capacity : 1 SATA in 6TB capacity	IRR 49,380,000
DS-7108NI-Q1/8P/M		IP video input : 8-ch 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 60 Mbps - HDMI output : 1920 1080p/60Hz - Capacity : 1 SATA in 6TB capacity	call












DS-7608NI-Q2/8P		IP video input : 8-ch / 8-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 2 SATA in	8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 80 Mbps - 6TB capacity disk	call
DS-7608NI-Q1		POE Up to x	8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats 1-ch @ 8 MP/3-ch @ 4 MP/6-ch @ 1080p decoding capacity Mbps incoming bandwidth	IRR 35,500,000
DS-7608NI-Q2		Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch @ 8 MP/3-ch @ 4 MP/6-ch @ 1080p decoding capacity Mbps incoming bandwidth		IRR 61,800,000
DS-7608NI-K1		IP video input : 8-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 1 SATA in	8-ch 1U 8 4K NVR Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 80 Mbps - 6TB capacity disk	IRR 68,340,000
DS-7608NI-K1/8P		Up to x	PoE 8-ch IP camera inputs interface Up to	IRR 126,190,000
DS-7608NI-K2		1-ch @ 8 MP/3-ch @ 4 MP/6-ch @ 1080p decoding capacity 2 HDMI and 1 VGA interfaces, 2 independent video output 2 SATA interfaces for HDD connection (u 10 TB capacity) 80 Mbps incoming bandwidth	8-ch 1U 4K NVR Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats 1-ch @ 8 MP/3-ch @ 4 MP/6-ch @ 1080p decoding capacity	IRR 52,280,000
DS-7608NI-K2/8P		IP video input : 8-ch / 8-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 2 SATA in	Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 80 Mbps - 6TB capacity disk	call
POE Up to x interface Up to for each				
DS-7616NI-Q1		IP video input : 16-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 1 SATA in	8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 160 Mbps - 6TB capacity disk	IRR 48,200,000
DS-7616NI-Q2		IP video input : 16-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 2 SATA in	Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 160 Mbps - 6TB capacity disk	IRR 89,810,000
DS-7616NI-Q2/16P		IP video input : 16-ch / 16-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 2 SATA in	8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 160 Mbps - 6TB capacity disk	IRR 107,470,000
DS-7616NI-K1		POE Up to x	16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats 1-ch @ 8M 5-ch @ 1080p decoding capacity Mbps incoming bandwidth	IRR 74,000,000
DS-7616NI-K2		IP video input : 16-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 2 SATA in	Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 160 Mbps - 6TB capacity disk	IRR 83,360,000
DS-7616NI-K2/16P		IP video input : 16-ch / 16-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 2 SATA in	8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 160 Mbps - 6TB capacity disk	call
DS-7716NI-Q4		IP video input : 16-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 4 SATA in	POE Up to x 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 160 Mbps - 6TB capacity disk	IRR 178,100,000
DS-7716NI-Q4/16P		IP video input : 16-ch / 16-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 4 SATA in	8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 160 Mbps - 6TB capacity disk	IRR 255,140,000
DS-7716NI-K4		IP video input : 16-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 4 SATA in	POE Up to x 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 160 Mbps - 6TB capacity disk	IRR 119,640,000
DS-7716NI-K4/16P		IP video input : 16-ch / 16-ch HDMI output : 4K (3840 2160)/30Hz - Capacity : 4 SATA in	8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 160 Mbps - 6TB capacity disk	call
POE Up to x interface Up to for each				
DS-8616NI-K8		Up to	16-ch 2U 4K NVR, 16 channel IP cameras can be connected. Supports decoding H.265+/H.265/H.264+/H.264/MPPEG4 video formats 4K high-definition live view, storage and playback. 160 Mbps high incoming bandwidth ensures IP cameras can be used for continuous video recording. Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera	IRR 147,000,000

Up to

Up to

HDD can be u

be con

DS-7732NI-Q4		IP video input : 32-ch 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 200 Mbps - HDMI output : 1920 x 1080/60Hz - Capacity : 4 SATA in 6TB capacity disk	IRR 119,500,000
IDS-7732NXI-I4/8S		Up to 32-ch 1.5U 4K DeepinMind NVR, H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on face Uplifting algorithm for each camera 16-ch perimeter protection 8-ch facial recognition video stream, or up to 16-ch facial recognition capture 8-ch video	IRR 636,180,000
DS-7732NI-Q4/16P		IP video input : 32-ch / 16-ch 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 200 Mbps - HDMI output : 1920 x 1080/60Hz - Capacity : 4 SATA in 6TB capacity disk Up to 16-ch for face pl	IRR 170,000,000
DS-7732NI-K4		IP video input : 32-ch 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 4 SATA in 6TB capacity disk	IRR 210,310,000
DS-7732NI-K4/16P		IP video input : 32-ch / 16-ch 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 x 2160)/30Hz - Capacity : 4 SATA in 6TB capacity disk	IRR 334,310,000
DS-8632NI-K8		POE Up to 32 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats for each camera 4K high-definition live view, storage and playback 160 Mbps high incoming bandwidth ensures IP cameras can be connected 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera	IRR 218,820,000
DS-9632NI-I8		Up to 32-ch 2U 4K NVR, 32 channel IP cameras can be connected, 12 MP high-definition live view, storage and playback 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected, 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks Up to HDD can be used	IRR 626,320,000
DS-9632NI-I16		Up to 32-ch 3U 4K NVR, 32 channel IP cameras can be connected, 12 MP high-definition live view, storage and playback 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected, 2 HDMI (different source) and 2 VGA (different source) interfaces 16 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks Up to HDD can be used	IRR 715,640,000
IDS-9632NXI-I8/4F		Facial Recognition and Comparison, Face Picture Library, 16 Libraries, 100,000 Pictures • Face Capture Analysis, Classification and Comparison and Alarm, • 4-ch Pictures Comparison Alarm, Alarm Linkage Actions: Recording, Audio Warning, Notify Surveillance Center, Send E-mail, • Face Picture Search, False Alarm Filtering 32 Channel IP Video Input • Incoming Bandwidth 256 Mbps, Outgoing Bandwidth 200 Mbps • Recording Resolution up to 12 MP, • Synchronous 2-ch HDMI, 2-ch VGA and HDMI1.4 (3840x2160) Resolution • H.265+/H.265/H.264+/H.264/MPEG4, Self-Adaptive Video Formatting • HDD Hot Swap with RAID0, RAID1, RAID5, RAID6, and RAID10 Storage Configuration 1 eSATA interface • Up to 16 Alarm Inputs, 4 Outputs, 1 Audio Output	IRR 2,843,060,000
DS-9664NI-I8		Up to 64-ch 2U 4K NVR, 64 channel IP cameras can be connected, 12 MP high-definition live view, storage and playback 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected, 2 HDMI (different source) and 2 VGA (different source) interfaces 8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks Up to HDD can be used	IRR 682,530,000
DS-9664NI-I16		Up to 64-ch 3U 4K NVR, 64 channel IP cameras can be connected, 12 MP high-definition live view, storage and playback 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected, 2 HDMI (different source) and 2 VGA (different source) interfaces 16 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition) camera/fisheye camera Advanced streaming technology enables smooth live view in network conditions Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks Up to HDD can be used	IRR 1,029,160,000