
















































Turbo HD Camera - DVR

















Items	Description	User Price
Turbo HD - 2MP		
DS-2CE56C0T-IRP	 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	IRR 5,680,000
DS-2CE56C0T-IRPF	 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR - Switchable TVI/AHD/CVI/CVBS	IRR 6,110,000
DS-2CE16D0T-ITF	 2 MP high performance CMOS - 1920 x 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR	IRR 8,070,000
DS-2CE16D0T-ITFS	 2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable, EXIR 2.0, advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 17,620,000
DS-2CE10DF3T-F ColorVu	 2 MP ColorVu Fixed Mini Bullet Camera 2 MP full time color bullet camera, 24/7 full color imaging, Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 24,220,000
DS-2CE10DF3T-FS	 2 MP ColorVu Audio Fixed Mini Bullet Camera High quality imaging with 2 MP, 1920 x 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images, Water and dust resistant (IP67) High quality audio with audio over coaxial cable, built-in mic One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	IRR 34,070,000
DS-2CE10DF3T-F	 DS-2CE10DF3T-F Turbo HD Products Turbo HD Cameras Turbo HD Cameras with ColorVu 2 MP ColorVu Fixed Mini Bullet Camera High quality imaging with 2 MP, 1920 x 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images	IRR 21,020,000
DS-2CE12DF3T-E ColorVu	 2 MP ColorVu Fixed Bullet Camera 24/7 full color imaging, Warm supplemental light with 40 m range 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 29,610,000
DS-2CE12DF3T-FS 2.8MM	 High quality imaging with 2 MP, 1920 x 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS)	IRR 38,330,000
DS-2CE16D0T-EXIP	 2MP Outdoor EXIR Fixed Mini Bullet Camera High quality imaging with 2 MP, 1920 x 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging, DWDR, 2DDNR Water and dust resistant (IP66)	IRR 6,144,000
DS-2CE16D0T-EXIPF 2.8mm	 2 MP Fixed Mini Bullet Camera, High quality imaging with 2 MP, 1920 x 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP66)	IRR 6,440,000
DS-2CE16D0T-ITF	 2 MP Fixed Mini Bullet Camera 2 MP bullet camera Smart IR: up to 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 8,070,000
DS-2CE16D0T-ITPF	 2 MP Fixed Mini Bullet Camera 2 MP, 1920 x 1080 resolution, 2.8 mm, 3.6 mm, 6 mm fixed lens 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) Smart IR, up to 25 m IR distance, DWDR, HLC, BLC	IRR 7,920,000



















DS-2CE16D0T-ITPFS		2 MP Audio Fixed Mini Bullet Camera 2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 25 m IR distance Water and dust resistant (IP67)	IRR 16,390,000
DS-2CE16D0T-EXIF		2 MP Fixed Mini Bullet Camera High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens, DWDR, 2DDNR Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP66)	IRR 12,980,000
DS-2CE16D0T-VFIR3F		2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 28,780,000
DS-2CE76D0T-ITPF		2 MP turret camera. EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 11,250,000
DS-2CE76D0T-ITPFS		2 MP Audio Fixed Turret Camera 2 MP coaxial audio camera, Enhancing safety with discreet and economical built-in microphone, Transmits audio over the coaxial cable. EXIR 2.0: advanced infrared technology with 30 m IR distance. Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 14,840,000
DS-2CE76D0T-ITMF		2 MP Fixed Turret Camera 2 MP turret camera EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 16,440,000
DS-2CE76D0T-ITMFS		2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 18,810,000
DS-2CE76D0T-EXIPF		High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm fixed lens Up to 20 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS)	IRR 13,390,000
DS-2CE70DF0T-PF-ColorVu		2 MP ColorVu Indoor Fixed Turret Camera High quality imaging with 2 MP, 1920 × 1080 resolution, 24/7 color imaging with F1.0 aperture 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS)	IRR 20,730,000
DS-2CE70DF3T-PF		2 MP ColorVu Fixed Turret Camera High quality imaging with 2 MP, 1920 × 1080 resolution, 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images. 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS)	IRR 26,980,000
DS-2CE72DF3T-E		2 MP ColorVu Fixed Turret Camera, High quality imaging with 2 MP, 1920 × 1080 resolution 24/7 color imaging with F1.0 aperture Clear imaging against strong back light due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images 2.8 mm, 3.6 mm, 6 mm fixed focal lens, Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	IRR 25,410,000
DS-2CE72KF0T-ES		High quality imaging with 3K, 2960 × 1665 resolution 24/7 colour imaging with F1.0 aperture 2.8 mm, 3.6 mm fixed focal lens Up to 40 m white light distance for bright night imaging High quality audio with audio over coaxial cable, built-in mic One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	IRR 37,400,000
DS-2CE72DFT-E		2 MP ColorVu Fixed Turret Camera 2 MP full time color turret camera 24/7 full color imaging Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67)	IRR 17,290,000
DS-2CE72DFT-FC		2 MP ColorVu Fixed Turret Camera, 2 MP full time color turret camera 24/7 full color imaging Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 10,520,000
DS-2CE10KF0T-ES		3K ColorVu Audio Fixed Mini Bullet Camera High quality imaging with 3K, 2960 × 1665 resolution 24/7 color imaging with F1.0 aperture 2.8 mm, 3.6 mm fixed focal lens Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	IRR 38,370,000
DS-2CE12KF0T-ES		High quality imaging with 3K, 2960 × 1665 resolution 24/7 color imaging with F1.0 aperture 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67) High quality audio with audio over coaxial cable, built-in mic	IRR 40,260,000
DS-2CE56D0T-VFIR3F		2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 32,240,000

DS-2CE76D3T-ITPF (NEW)		2 MP Ultra Low Light Indoor Fixed Turret Camera, 2 MP turret camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology. 3D DNR technology delivers clean and sharp images. EXIR 2.0: advanced infrared technology with 30 m IR distance, 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 17,420,000
DS-2CE16D3T-ITF		2 MP Ultra Low Light Fixed Mini Bullet Camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology. 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 21,660,000
DS-2CE16D3T-IT3F		2 MP bullet camera Strong night performance, capturing images in ultra-low light down to 0.005 lux Clear imaging even against strong back lighting due to 120 dB true WDR technology. 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 50 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 19,670,000
DS-2CE16D8T-IT3E		2 MP Ultra Low Light PoC Fixed Bullet Camera 2 MP high performance bullet camera Strong night performance, capturing images in ultra-low light down to 0.003 lux Clear imaging even against strong back lighting due to 130 dB true WDR technology. 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 60 m IR distance Water and dust resistant (IP67) Transmits both HD video and power over the same coaxial cable	IRR 21,600,000
DS-2CE16D3T-13F		2 MP high-performance CMOS . Ultra low light . 1920 × 1080 resolution . 2.8 mm, 3.6 mm, 6 mm fixed lens . Smart IR, up to 30 m IR distance . OSD menu, 3D DNR, 120 dB true WDR, day/night switch . 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) . IP67 . Up the coax (HIKVISION-C)	IRR 12,400,000
DS-2CE56F7T-IT3Z		3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8-12mm motorized vari-focal lens - True Day/Night - OSD menu, DNR, Smart IR - True WDR, up to 120dB - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 34,900,000
DS-2CE16H0T-ITF		5 MP Fixed Mini Bullet Camera, 5 MP bullet camera EXIR 2.0: advanced infrared technology with 20 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 19,470,000
DS-2CE16H0T-ITFS		5 MP Audio Fixed Mini Bullet Camera, 5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone. Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 23,050,000
DS-2CE16H0T-ITPFS		5 MP Audio Fixed Mini Bullet Camera 5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 25 m IR distance Water and dust resistant (IP67)	IRR 20,770,000
DS-2CE16H0T-ITPF		5 MP Fixed Mini Bullet Camera 5 MP bullet camera EXIR 2.0: advanced infrared technology with 20 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 15,690,000
DS-2CE16H0T-IT1F		5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 14,030,000
DS-2CE17H0T-IT1E		5 MP Fixed Bullet Camera High quality imaging with 5 MP, 2560 × 1944 resolution 2.4 mm, 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 30 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	IRR 23,230,000
DS-2CE17H0T-IT3E		5 MP Fixed Bullet Camera High quality imaging with 5 MP, 2560 × 1944 resolution 2.8 mm, 3.6 mm, 6 mm, 8mm, 12mm fixed focal lens Up to 40 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	IRR 20,610,000
DS-2CE17H0T-IT3FS		High quality imaging with 5 MP, 2560 × 1944 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 40 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67) High quality audio with audio over coaxial cable, built-in mic	IRR 29,790,000
DS-2CE17H0T-IT5E		5 MP Fixed Bullet Camera High quality imaging with 5 MP, 2560 × 1944 resolution 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens Up to 80 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	IRR 18,500,000
DS-2CE16H0T-IT3E		5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 14,380,000
DS-2CE16H0T-IT5E		5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 16,690,000



DS-2CE16H0T-IT3ZF		5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 28,750,000
DS-2CE17D0T-IT1F		2 MP Fixed Bullet Camera High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens Up to 30 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	IRR 18,050,000
DS-2CE17D0T-IT3F		2 MP Fixed Bullet Camera High quality imaging with 2 MP, 1920 × 1080 resolution 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens Up to 40 m IR distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) Water and dust resistant (IP67)	IRR 23,160,000
DS-2CE10HFT-F28		5 MP ColorVu Fixed Mini Bullet Camera, 5 MP full time color bullet camera 24/7 full color imaging, 2.8 mm fixed focal lens Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 24,630,000
DS-2CE10DF0T-F		2 MP ColorVu Fixed Mini Bullet Camera. High quality imaging with 2 MP, 1920 × 1080 resolution. 24/7 color imaging with F1.0 aperture. 3D DNR technology delivers clean and sharp images. 2.8 mm, 3.6 mm, 6 mm fixed focal lens. Up to 20 m white light distance for bright night imaging.	IRR 28,420,000
DS-2CE12HFT-F28 2.8mm		5 MP ColorVu Fixed Bullet Camera, 5 MP full time color bullet camera 24/7 full color imaging, 2.8 mm fixed focal lens Warm supplemental light with 40 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 27,950,000
DS-2CE72HFT-F28		5 MP ColorVu Fixed Turret Camera, 5 MP full time color turret camera 24/7 full color imaging, 2.8 mm fixed focal lens Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 33,940,000
DS-2CE76H0T-ITMF		5 MP coaxial - Enhanced safety with discreet and economical Transmit audio over coaxial cable. EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 21,440,000
DS-2CE76H0T-ITMFS		5 MP coaxial audio camera, Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable. EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 24,290,000
DS-2CE76H0T-ITPF		5 MP Indoor Fixed Turret Camera 5 MP turret camera EXIR 2.0: advanced infrared technology with 20 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 16,300,000
DS-2CE78D0T-IT3FS		2 MP Audio Fixed Turret Camera, 2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 23,840,000
DS-2CE78D3T-ITMF		2 MP Ultra Low Light Fixed Turret Camera, 2 MP turret camera Strong night performance, capturing images in ultra-low light down to 0.005 lux. Clear imaging even against strong back lighting due to 120 dB true WDR technology 3D DNR technology delivers clean and sharp images EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 23,840,000
DS-2CE78D0T-ITFS			IRR 16,880,000
DS-2CE76H0T-ITPFS		5 MP coaxial audio camera Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable EXIR 2.0: advanced infrared technology with 20 m IR distance 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 20,280,000
DS-2CE78H0T-IT1F 2.4mm		5 MP Camera 5 MP, 2560 × 1944 resolution 2.4 mm, 2.8 mm, 3.6 mm, 6 mm fixed focal lens Smart IR, up to 30 m IR distance 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) IP67	IRR 23,860,000
DS-72HFT-F28		5 MP ColorVu Fixed Turret Camera, 5 MP full time color turret camera 24/7 full color imaging, 2.8 mm fixed focal lens Warm supplemental light with 20 m range Clear imaging even against strong back lighting due to 130 dB true WDR technology 3D DNR technology delivers clean and sharp images Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 28,920,000










DS-2CE78H0T-IT3F0		5 MP turret camera EXIR 2.0: advanced infrared technology with 40 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 25,790,000
DS-2CE56H0T-ITMF		5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 13,620,000
DS-2CE56H0T-IT1F		5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 14,410,000
DS-2CE56H0T-IT3F		5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 15,570,000
DS-2CE56H0T-IT3ZF		5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 31,510,000
DS-2CE71H0T-PIRL		5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 15,270,000
DS-2CE78U8T-IT3		4K Ultra-Low Light Turret Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 63,870,000
DS-2CE18U8T-IT3		4K Ultra-Low Light Bullet Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 53,730,000
DS-2AE4225TI-D		High quality imaging with 2 MP resolution - Excellent low-light performance via powered-by-DarkFighter technology -Clear imaging against strong back lighting due to 120 dB WDR technology - Pan and tilt ability enables camera to monitor zones of interest - 25 × optical zoom allows for closer viewing of subjects in expansive areas - Up to 100 m IR range ensures safety at night - Water and dust resistant (IP66)	IRR 180,520,000
DS-2AE5223TI-A (24VAC)		1/3" CMOS, 1920x1080:30fps, TVI & CVBS dual output - 3D DNR, ICR, Color: 0.05Lux/F1.4, B/W:0.005Lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1°~400°/s, Tilt Speed: 0.1°~120°/s, Up the Coax, 150m IR	call
DS-2AE7230TI-A (24VAC)		High performance 1/3" CMOS - Max. image resolution: 1920 × 1080 - Min. illumination: Color: 0.05Lux @ (F1.6, AGC ON); B/W: 0.005Lux @ (F1.6, AGC ON); 0 Lux with IR - 30× optical zoom, focal length 4-120mm - 16× digital zoom - 120m IR distance - IR cut filter - 3D DNR, Digital WDR, BLC - TVI and CVBS dual output	call
DS-7204HQHI-K1		Analog video input 4-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 29,780,000
IDS-7204HQHI-M1/S		4-ch 1080p 1U H.265 AcuSense DVR 4 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps, 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 6 network cameras can be connected.	IRR 46,520,000
IDS-7204HUHI-M1		4-ch 5 MP 1U H.265 AcuSense DVR 4 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 8 MP lite @ 15 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 8 network cameras can be connected.	IRR 35,573,000
DS-7208HQHI-K1		Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 38,370,000
IDS-7208HQHI-M1/S		8-ch 1080p 1U H.265 AcuSense DVR 8 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 12 network cameras can be connected.	IRR 71,290,000



DS-7208HUHI-M1/S		8-ch 5 MP 1U H.265 AcuSense DVR 8 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 8 MP @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 16 network cameras can be connected.	IRR 106,700,000
DS-7116HQHI-K1		Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD14CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate : 4 MP lite@15fps; 1080p lite/720p/WD14CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 6 TB capacity	IRR 56,500,000
IDS-7216HUHI-M2/S		16-ch 5 MP 1U H.265 AcuSense DVR Deep learning-based motion detection 2.0 for all analog channels Deep learning-based perimeter protection Efficient H.265 pro+ compression technology Encoding ability up to 8 MP @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 32 network cameras can be connected	IRR 198,240,000
IDS-7216HQHI-M1/S		16-ch 1080p 1U H.265 AcuSense DVR 16 channels and 1 HDD 1U AcuSense DVR False alarm reduction through human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 24 network cameras can be connected.	IRR 109,770,000
IDS-7216HQHI-M2/S		Record from and Manage up to 16 Cameras Supports up to 8 IP Channels Up to 2MP Recording Resolution 20TB HDD Capacity (Available Separately) H.265+/H.264+/H.265/H.264 Video Codecs Two-Way Audio HDMI & VGA Video Outputs	IRR 151,150,000
7216HQHI-K1-Eco		Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD14CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate : 4 MP lite@15fps; 1080p lite/720p/WD14CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity - ECO CASE	call
DS-7216HQHI-K1		Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD14CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate : 4 MP lite@15fps; 1080p lite/720p/WD14CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 107,750,000
DS-7208HGHI-F1		8-ch 1080p Lite 1U H.264 DVR 8 channels and 1 HDD 1U DVR H.264+ / H.264 video compression Encoding ability up to 1080p lite @ 25/30 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 10 network cameras can be connected	IRR 30,110,000
DS-7208HGHI-F2		8-ch 1080p Lite 1U H.264 DVR 8 channels and 2 HDDs 1U DVR H.264+ / H.264 video compression Encoding ability up to 1080p lite @ 25/30 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 10 network cameras can be connected	IRR 39,720,000
DS-7216HGHI-K1		16-ch 1080p Lite 1U H.265 DVR Deep learning based human and vehicle targets classification of Motion Detection 2.0H.265 Pro+/H.265 Pro/H.265 video compressionHDTV/AHD/CVI/CVBS/IP video inputAudio via coaxial cable Up to 18-ch IP camera inputs (up to 5 MP)/Up to 1080p Lite@15 fps encoding capability Max. 1200 m for 720p HDTV signal	IRR 63,930,000
DS-7216HQHI-K2		Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD14CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate : 4 MP lite@15fps; 1080p lite/720p/WD14CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	IRR 87,850,000
IDS-7232HQHI-M2/S		32-ch 1080p 1U H.265 AcuSense DVR Deep learning-based motion detection 2.0 for all analog channels Deep learning-based perimeter protection Efficient H.265 pro+ compression technology Encoding ability up to 1080p @ 15 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 40 network cameras can be connected	IRR 219,660,000
DS-7232HQHI-K2		Analog video input 32-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD14CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate : 4 MP lite@15fps; 1080p lite/720p/WD14CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 40-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	IRR 267,320,000
DS-7204HUHI-K1		Analog video input 4-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD14CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - Frame rate : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD14CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 4-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 67,720,000
DS-7208HUHI-K1		Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD14CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD14CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 × 2160)/30Hz - Audio input 4-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 70,930,000
IDS-7204HUHI-M1/S		4-ch 5 MP 1U H.265 AcuSense DVR, 4 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 8 MP lite @ 15 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP) Up to 8 network cameras can be connected.	IRR 74,720,000



<p>IDS-7208HUHI-M1/S</p>		<p>8-ch 5 MP 1U H.265 AcuSense DVR, 8 channels and 1 HDD 1U AcuSense DVR False alarm reduction by human and vehicle target classification based on deep learning Efficient H.265 pro+ compression technology Encoding ability up to 8 MP @ 8 fps, 5 MP @ 12 fps 5 signals input adaptively (HDTV/AHD/CVI/CVBS/IP), Up to 16 network cameras can be connected.</p>	<p>IRR 120,610,000</p>
<p>DS-7316HUHI-F4/N</p>		<p>Support HD-TVI, AHD and analog cameras with adaptive access 16 Composite Video Inputs, 1 Composite Video Output, 1 VGA Output & Dual HDMI Output TVI 720P / 1080P, AHD 720P, IP Video Input: 2Ch up to 8MP Support 4 Units SATA Harddisk (Max 6TB per unit) Support USB Flash Drive Backup, Network Remote Recording & Back-up Remote surveillance with IE Browser & Mobile Phone Apps Support TCP/IP, PPPoE, DHCP, DDNS, UPnP, HTTPS & Hik Cloud P2P</p>	<p>IRR 395,660,000</p>
<p>DS-7216HUHI-K2</p>		<p>Analog video input 16-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u>: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u>: 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk</p>	<p>IRR 218,730,000</p>
Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP			
<p>DS-7204HUHI-K1/P</p>		<p>Analog video input 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u>: 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u>: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u>: 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - <u>Provide power supply to PoC cameras over coaxial cable</u></p>	<p>IRR 59,680,000</p>
<p>DS-7208HUHI-K2/P</p>		<p>Analog video input 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u>: 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u>: 8-ch (up to 12-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk - <u>Provide power supply to PoC cameras over coaxial cable</u></p>	<p>IRR 115,230,000</p>
Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP			
<p>DS-7204HHTHI-K1</p>		<p>Analog video input 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Full channel recording at Up to 8 MP resolution</u> - <u>Frame rate</u>: 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u>: 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity</p>	<p>IRR 71,230,000</p>
<p>DS-7208HHTHI-K2</p>		<p>Analog video input 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u>: 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u>: 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 x 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk</p>	<p>IRR 113,250,000</p>