























































Hilook-NVR			
Items	Description	User Price	
1	<a href="#">IPC-B120</a> 1/2.8" progressive scan CMOS-1920 × 1080@30fps -2.8 mm fixed lens- H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR	CALL	
2	<b>IPC-B120-D/W</b> 2 MP Outdoor Fixed Bullet Network Camera with <b>Build-in Mic</b> High quality imaging with 2 MP resolution Efficient H.264 compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology Built-in microphone for real-time audio security <b>Wireless connection</b> for convenient installation and use	CALL	
3	<a href="#">IPC-B120H</a> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lens BLC, DC12V & PoE,-up to 30m IR- Support mobile monitoring via Hik-Connec *power supply no included-DWDR-Front Cover: Metal- Back Cover & Bracket: Plastic-IP67	IRR 18,770,000	
4	<b>IPC-B121H</b> 1/2.8" progressive scan CMOS 3D DNR 1920 × 1080@30fps Up to 30 m IR range 2.8 mm/4 mm fixed lens IP67, DWDR, H265	IRR 18,290,000	
5	<a href="#">IPC-B121H-M</a> 2 MP Fixed Bullet Network Camera High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology, (IP67) EXIR 2.0: advanced infrared technology with long IR range	CALL	
6	<a href="#">IPC-B140H</a> 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, ConneC *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 22,680,000	
7	<b>IPC-B140H-M</b> 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, ConneC *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	CALL	
8	<b>IPC-B150H</b> High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 29,260,000	
9	<a href="#">IPC-B220</a> 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application	IRR 18,770,000	
10	<a href="#">IPC-B220-D</a> 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply	IRR 17,930,000	
11	<a href="#">IPC-T120</a> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),DWDR -H.264 +&H.264,-2.8/4/6mm fixed lens- BLC, - DC12V & PoE ,-up to 10m IR- Support mobile monitoring via Hik-Connect *power supply no included-Eyeball:Plastic-Cover: Plastic-Indoor-ip67	IRR 18,290,000	
12	<a href="#">IPC-T120-D</a> 1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply	IRR 17,560,000	
13	<a href="#">IPC-T220-H</a> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWDR, BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via HikConnec *power supply no included2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67	IRR 20,080,000	
14	<b>IPC-T221-H</b> 2 MP Fixed Turret Network Camera High quality imaging with 2 MP resolution,Efficient H.265+ Clear imaging against ,strong back light by DWDR technology Water and dust resistant (IP67) (PoE) technology	IRR 20,800,000	
15	<b>IPC-T220</b> 1/2.8" progressive scan CMOS BLC/3D DNR,1920 × 1080@30fps,IP67 2.8, 4, 6 mm fixed lens,Digital WDR,H.264+, H.264 Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON);	IRR 19,600,000	
16	<a href="#">IPC-T240H</a> 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE-2.8/4/6mm fixed lens,-Support mobile monitoring via Hik-Connec *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 27,000,000	

17	<a href="#">IPC-D120</a>	1/2.8" progressive scan CMOS-2 MP-1920 × 1080@30fps-2.8mm fixed lens-H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 18,660,000	
18	<a href="#">IPC-D120H</a>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, --2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10	CALL	
19	<a href="#">IPC-D121H</a>	2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology	IRR 18,290,000	
20	<a href="#">IPC-D121H-M</a>	2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology <b>METAL CASE</b>	IRR 18,290,000	
21	<a href="#">IPC-D140H</a>	4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps □ Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 □ IP67, IK10, Dual stream, 120 dB WDR.	IRR 27,000,000	
22	<a href="#">IPC-D150H</a>	High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) and vandal resistant (IK10) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	CALL	
23	<a href="#">IPC-B620H-V</a>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot,up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 38,190,000	
24	<a href="#">IPC-B620H-Z</a>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 42,800,000	
25	<a href="#">IPC-B621-V</a>	2 MP Varifocal Bullet Network Camera Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology(IP66) -V: model with manual vari-focal lens Built-in microphone enhances safety with video/audio in tandem	IRR 36,940,000	
26	<a href="#">IPC-B621-Z</a>	2 MP Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Efficient H.265+ Clear imaging against strong back light due to DWDR technology(IP66) -Z: model with motorized vari-focal lens Built-in microphone enhances safety with video/audio in tandem	IRR 42,060,000	
27	<a href="#">IPC-B640H-V</a>	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot, WDR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 39,800,000	
28	<a href="#">IPC-B640H-Z</a>	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot,-WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 47,550,000	
29	<a href="#">IPC-T620-Z</a>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC,-WDR- up to 30m IR-DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included2.8~12mm VF lens-Eyeball: MetalCover: Plastic-IP67	IRR 43,160,000	
30	<a href="#">IPC-D620H-V</a>	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264,DWDR- 3D DNR, BLC,2.8~12mm varifocal lens - DC12V & PoE, TF card slot,-up to 30m IR-- Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10	IRR 38,190,000	
31	<a href="#">IPC-D620H-Z</a>	1/2.8" progressive scan CMOS-2 MP-1920 × 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream- DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10	IRR 46,820,000	
32	<a href="#">IPC-D640H-V</a>	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot- --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 41,480,000	
33	<a href="#">IPC-D640H-Z</a>	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot- --2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	CALL	

PanoVu Mini Series IR Network PTZ Camera				
34	<a href="#">PTZ-P332ZI-DE3</a>	<p>System Functions</p> <ul style="list-style-type: none"> <li>3-ch panoramic images in different directions and 1-ch close-up image</li> <li>PTZ linkage Up to 10 m IR radius</li> <li>Panoramic Camera Three 1/2.8" progressive scan CMOS 3-ch 1920 × 1080@30fps resolution</li> <li>Horizontal FOV: 128.5° × 3</li> <li>PTZ Camera 1/2.8" progressive scan CMOS Up to 1920 × 1080@30fps resolution</li> <li>4× optical zoom, 8× digital zoom</li> </ul>	CALL	
IP PTZ Camera				
35	<a href="#">PTZ-N4215-DE3</a>	<p>1/2.8" progressive scan CMOS</p> <ul style="list-style-type: none"> <li>Up to 1920 × 1080 resolution</li> <li>Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON)</li> <li>B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR</li> <li>15× optical zoom, 16× digital zoom</li> <li>120dB WDR, 3D DNR, HLC, BLC</li> <li>12 VDC &amp; PoE+ (802.3at, class4)</li> <li>Support H.265+/H.265 video compression</li> <li>Up to 24 programmable privacy masks</li> <li>Support ROI</li> </ul>	CALL	
36	<a href="#">PTZ-N4215I-DE</a>	<p>1/2.8" progressive scan CMOS</p> <ul style="list-style-type: none"> <li>Up to 1920 × 1080 resolution</li> <li>Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON)</li> <li>B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR</li> <li>Up to 100 m IR distance</li> <li>15× optical zoom, 16× digital zoom</li> <li>120dB WDR, 3D DNR, HLC, BLC, Smart IR</li> <li>12 VDC &amp; PoE+ (802.3at, class4)</li> <li>Support H.265+/H.265 video compression</li> <li>Up to 24 programmable privacy masks</li> <li>Support ROI</li> </ul>	IRR 79,500,000	
37	<a href="#">PTZ-N4225I-DE</a>	<p>1/2.8" progressive scan CMOS</p> <ul style="list-style-type: none"> <li>Up to 1920 × 1080 resolution</li> <li>Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON)</li> <li>B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR</li> <li>Up to 100 m IR distance</li> <li>25× optical zoom, 16× digital zoom</li> <li>120dB WDR, 3D DNR, HLC, BLC, Smart IR</li> <li>12 VDC &amp; PoE+ (802.3at, class4)</li> <li>Support H.265+/H.265 video compression</li> <li>Up to 24 programmable privacy masks</li> <li>Support ROI</li> </ul>	IRR 99,400,000	
38		<p>Two-inch 4 MP camera with pan, tilt and zoom (4x) ability</p> <ul style="list-style-type: none"> <li>Efficient H.265+ compression technology to save bandwidth and storage</li> <li>Clear imaging against strong back light due to 120 dB true WDR technology</li> <li>Great night-time performance with up to 20 m enhanced IR</li> <li>Water and dust resistant (IP66), and vandal proof (IK10)</li> </ul>	CALL	
Network Video Recorder				
39	<a href="#">NVR-104-B</a>	<p>Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video), Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@ 4MP-4-ch@1080p</p>	IRR 15,150,000	
40	<a href="#">NVR-108-B</a>	<p>Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video), Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p</p>	IRR 18,440,000	
41	<a href="#">NVR-108-B/8p</a>	<p>4-ch Mini 1U 4 PoE 4K NVR, Up to 8 channel IP cameras can be connected</p> <ul style="list-style-type: none"> <li>Plug &amp; Play with 8 Power-over-Ethernet (PoE) interfaces</li> <li>Supports decoding H.264+/H.264 multiple video formats</li> <li>Up to 4-ch @ 1080p decoding capacity</li> <li>1 HDD for continuous video recording</li> </ul>	IRR 30,490,000	
42	<a href="#">NVR-104H-D</a>	<p>4-ch Mini 1U 4 PoE NVR</p> <ul style="list-style-type: none"> <li>H.265+/H.265/H.264+/H.264 video compression</li> <li>Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth</li> <li>Up to 4-ch network camera inputs, Up to 4-ch 1080p decoding capability</li> <li>HDMI and VGA simultaneous output</li> </ul>	IRR 14,370,000	
43	<a href="#">NVR-108H-D</a>	<p>4-ch Mini 1U NVR</p> <ul style="list-style-type: none"> <li>H.265+/H.265/H.264+/H.264 video compression</li> <li>Up to 60 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth</li> <li>Up to 8-ch network camera inputs, Up to 4-ch 1080p decoding capability</li> <li>HDMI and VGA simultaneous output</li> </ul>	IRR 18,290,000	
44	<a href="#">NVR-104MH-C</a>	<p>Recording at up to 8 MP resolution-40Mbps Bit Rate -Input Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB) interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p</p>	IRR 19,750,000	
45	<a href="#">NVR-104MH-D</a>	<p>Up to 4 channel IP cameras can be connected</p> <ul style="list-style-type: none"> <li>Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats</li> <li>Up to 4-ch @ 1080p decoding capacity</li> <li>1 HDD for continuous video recording.</li> </ul>	IRR 15,150,000	
46	<a href="#">NVR-104MH-D/4P</a>	<p>Up to 4 channel IP cameras can be connected</p> <ul style="list-style-type: none"> <li>Plug &amp; Play with 4 Power-over-Ethernet (PoE) interfaces</li> <li>Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats</li> <li>Up to 4-ch @ 1080p decoding capacity</li> <li>1 HDD for continuous video recording</li> </ul>	IRR 25,020,000	



47	<a href="#">NVR-104MH-C/4P</a>	Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP) ,Output Bandwidth 80Mbps- H.265-, 1SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P	CALL	
48	NVR-108MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)- HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 27,800,000	
49	NVR-108MH-D	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 18,440,000	
50	<a href="#">NVR-208MH-C</a>	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 2 SATA interface(6TB), standalone 1U 315 case(Metal)- HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 33,970,000	
51	<a href="#">NVR-108MH-C/8P</a>	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP tp 8mp),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6 TB),8 independent PoE network interfaces, standalone 1U 315 case(Metal)-HDMI Output 1ch 4k, - Decoding Capability:1-ch @ 8 MP / 4-ch @ 1080p	CALL	
52	NVR-108MH-D/8P	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 47,500,000	
53	<a href="#">NVR-116MH-C</a>	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 29,630,000	
54	<a href="#">NVR-216MH-C</a>	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video),Output Bandwidth 80Mbps, - H.265-2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	CALL	
55	<a href="#">NVR-216MH-C/16P</a>	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video)Output Bandwidth 80Mbps, H.265, 2 SATA( up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k, -Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	CALL	