

1	<p>DH-IPC-HFW5842EP-ZE</p> 	<p>8MP IR Vari-focal Bullet WizMind Network Camera > 8MP 1/1.8" CMOS image sensor, low illuminance, high image definition (high definition image). > Outputs max. 8MP (3840× 2160) @30 fps. > Max. IR distance: 60 m. > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes > Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card. > 12V DC/PoE power supply. > ePoE, IP67, IK10 protection.> SMD 3.0</p>      	 <p>ریال ۲۷۲,۹۸۷,۰۰۰</p>
2	<p>DH-IPC-HFW5541EP-ZE</p> 	<p>5MP IR Vari-focal Bullet WizMind Network Camera > 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 5 MP (2592 × 1944)@20 fps. > Built-in IR LED, and the max. illumination distance is 60 m. > ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments. > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. > Three switchable intelligent resources: IVS, face detection, and people counting. > Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card. > 12 VDC/PoE power supply, easy for installation. > IP67 and IK10 protection; ePoE. > SMD 3.0.</p>      	 <p>ریال ۲۰۱,۹۲۰,۰۰۰</p>
3	<p>DH-IPC-HFW5541TP-ASE</p> 	<ul style="list-style-type: none"> • 1/2.7" 5Megapixel progressive scan CMOS • ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments • 20 fps@2592 × 1944, 50/60 fps@1080P (1920 × 1080) • WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS • 2.8 mm fixed lens (3.6 mm, 6.0 mm, 8.0 mm, 12.0 mm optional) • 1/1 Alarm in/out, 1/1 audio in/out • Max. IR LEDs Length 80 m • Micro SD memory, IP67,IK10     	 <p>ریال ۱۳۳,۷۱۶,۰۰۰</p>
4	<p>DH-IPC-HFW5442EP-ZE</p> 	<ul style="list-style-type: none"> • 1/1.8" 4Megapixel progressive scan CMOS (AI-SATRLIGHT) • H.265 & H.264 triple-stream encoding • 25/30 fps@2688 × 1520, 50/60 fps@1080P(1920 × 1080) • WDR (120 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS • 2.7 mm-12.0 mm motorized lens • 2/1 Alarm in/out, 1/1 audio in/out • Max. IR LEDs Length 50 m • Micro SD memory, IP67, IK10      	 <p>ریال ۲۳۱,۰۵۵,۰۰۰</p>
5	<p>DH-IPC-HFW3449EP-AS-LED</p> 	<ul style="list-style-type: none"> • 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition • Outputs max. 4MP (2688 × 1520) @ 30 fps • H.265 codec, high compression rate, low bit rate • Built-in Warm LED, max. LED distance: 30 m • ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments • Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes • Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) • Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection • Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic • 12V DC/PoE power support • IP67 protection · SMD Plus      	 <p>ریال ۸۶,۶۷۰,۰۰۰</p>

6

DH-IPC-HFW3441EP-SA



- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- Outputs max. 4MP (2688 × 1520)@30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in IR LED, max. IR distance: 50 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Supports max. 256 G Micro SD card, built-in Mic
- 12V DC/POE power supply
- IP67 protection · SMD Plus



ریال ۲۲,۱۸۰,۰۰۰

7

DH-IPC-HFW3441EP-AS



- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- Outputs max. 4MP (2688 × 1520)@30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in IR LED, max. IR distance: 50 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio abnormality detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Alarm: In, out; Audio: In, out; Supports max. 256 G Micro SD card, built-in Mic
- 12V DC/POE power supply
- IP67 protection · SMD Plus



ریال ۷۵,۴۰۰,۰۰۰

8

DH-IPC-HFW2831TP-ZS

- 1/1.8" 8Megapixel progressive CMOS STARLIGHT
- H.265 & H.264 dual-stream encoding
- 25/30fps@8MP(3840×2160)
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) &
- Micro SD card slot, up to 128GB; 3.7"11mm motorized lens
- Max IR LEDs Length 60m· IP67, IK10(optional), PoE



ریال ۵۱,۱۲۵,۰۰۰

9

DH-IPC-HFW2831SP-S

- 8MP Lite IR Fixed-focal Bullet Network Camera
- > 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
 - > Outputs max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps
 - > H.265 codec, high compression rate, ultra-low bit rate
 - > Built-in IR LED, max IR distance: 30 m
 - > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes> Intelligent detection: Intrusion, tripwire · Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection > Supports max. 256 GB Micro SD card> 12V DC/POE power supply> IP67 protection



ریال ۱۱,۸۳۰,۰۰۰

10	DH-IPC-HFW2531TP-ZS	<ul style="list-style-type: none"> · 1/2.7" 5Megapixel progressive CMOS STARLIGHT · H.265 & H.264 dual-stream encoding · 15fps@5M(2592x1944)&25/30fps@3M(2304x1296) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · IP67, PoE+ · 2.7~13.5mm motorized lens· Max IR LEDs Length 60m 		۱۲۲,۰۹۰,۰۰۰ ریال
11	DH-IPC-HFW2531SP-S	<ul style="list-style-type: none"> · 5MP Lite IR Fixed-focal Bullet Network Camera STARLIGHT · 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps · H.265 codec, high compression rate, ultra-low bit rate · Built-in IR LED, max IR distance: 30 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Intelligent detection: Intrusion, tripwire · Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection · Supports max. 256 GB Micro SD card · 12V DC/PoE power supply IP67 protection 		۷۰,۵۱۰,۰۰۰ ریال
12	DH-IPC-HFW2431TP-ZS	<ul style="list-style-type: none"> · 1/3" 4Megapixel progressive CMOS · H.265 & H.264 dual-stream encoding · 20fps@4M(2688x1520)&25/30fps@3M(2304x1296) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · 2.7~13.5mm motorized lens· Max IR LEDs Length 60m · IP67, IK10(optional), PoE+ 		۹۹,۹۴۶,۵۰۰ ریال
13	DH-IPC-HFW2431SP-S	<ul style="list-style-type: none"> · 4MP, 1/3" CMOS image sensor, low illuminance, Starlight · Outputs 4MP (2560 × 1440)@25/30fps, Max. supports 4MP (2688 × 1520)@20 fps · H.265 codec, high compression ration, ultra-low bit rate · Built-in IR LED, max IR distance: 30 m · ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Intelligent detection: Intrusion, tripwire · IP67 protection · Abnormality detection: Motion detection, video tampering, no SD · Supports max. 256 GB Micro SD card · 12V DC/PoE power support 		۵۵,۱۲۰,۰۰۰ ریال
14	DH-IPC-HFW2231TP-ZS	<ul style="list-style-type: none"> · 1/2.8" 2Megapixel progressive STARVIS™ CMOS · H.265 & H.264 dual-stream encoding · 25/30fps@1080P(1920x1080) · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · Micro SD card slot, up to 128GB · 2.7~13.5mm motorized lens· Max IR LEDs Length 60m · IP67, IK10(optional), PoE 		۸۸,۲۱۰,۰۰۰ ریال

15	DH-IPC-HFW1831EP	<ul style="list-style-type: none"> • 1/1.8" 8Megapixel progressive scan CMOS • H.265&H.264 dual-stream encoding • 25/30fps@8MP(3840×2160) • WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 2.8mm fixed lens (4mm, 6mm optional) • Max. IR LEDs Length 50m ·IP67, PoE 			۱۱۵,۴۳۰,۰۰۰ ریال
16	DH-IPC-HFW1431SP	<ul style="list-style-type: none"> • 1/3" 4Megapixel progressive CMOS • H.265 & H.264 dual-stream encoding • 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) • WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 2.8 mm fixed lens (3.6 mm optional) • Max IR LEDs Length 30m ·IP67, PoE 			۴۷,۵۰۵,۲۰۰ ریال
17	DH-IPC-HFW1431S1P	<ul style="list-style-type: none"> • 4MP, 1/3" CMOS image sensor, low illuminance, high image definition • Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps • H.265 codec, high compression rate, ultra-low bit rate • Built-in IR LED, max. IR distance: 30 m • ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments • Image flip, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes • Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection • 12V DC/PoE power support • IP67, protection 			۴۲,۶۷۴,۹۰۰ ریال
18	DH-IPC-HFW1230T1P-ZS	<ul style="list-style-type: none"> • 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition • Outputs max. 2MP (1920 × 1080p) @25/30 fps • H.265 codec, high compression rate, ultra-low bit rate • Built-in IR LED, max. IR distance: 50 m • ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments • Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes • Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access • Supports max. 256 GB Micro SD card • 12V DC/PoE power supply • IP67 protection 			۱,۵۳۶,۰۰۰ ریال
19	DH-IPC-HFW1230SP	<ul style="list-style-type: none"> • 1/2.7" 2Megapixel progressive CMOS • H.265& H.264 dual-stream encoding • 25/30fps@1080P(1920×1080) • DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 2.8 mm fixed lens (3.6mm optional) • Max IR LEDs Length 30m ·IP67, PoE 			۳۶,۹۱۰,۰۰۰ ریال

20	<p>IPC-A22EP</p> 	<p>Human Detection 1080P 360° Coverage Built-in Siren Smart Tracking Privacy Mode Abnormal Sound Alarm Night Vision Two-way Talk Cloud</p>		<p>۲۵,۱۲۰,۰۰۰ ریال</p>
21	<p>DH-IPC-K100W</p> 	<ul style="list-style-type: none"> • 1/3" 1.3Megapixel Aptina CMOS • H.264 & MJPEG dual-stream encoding • Max 15fps@1.3M (1280x960)/25/30fps@720P(1280x720) • DWDR, Day/Night, 2DNR, Auto iris, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 3.6mm fixed lens • White LEDs length 10m • PIR sensor range 6m • Micro SD memory . Wi-Fi 		<p>۲۹,۳۰۰,۰۰۰ ریال</p>
22	<p>DH-IPC-K22P</p> 	<ul style="list-style-type: none"> . 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition . Outputs max. 2MP (1920 × 1080) @25/30 fps . H.265 codec, high compression rate, ultra-low bit rate . Max. IR distance: 10 m . Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes . H.264/H.265, flexible coding, applicable to various bandwidth and storage environments. . Alarm: 1 in, 1 out; 256 G SD card, built-in Mic and speaker . Supports 256 G Micro SD card . 12V DC power supply, easy for installation . Supports PIR . Supports Wi-Fi 		<p>۳۷,۸۳۰,۰۰۰ ریال</p>
23	<p>DH-IPC-HDBW5842EP-ZE</p> 	<p>8MP IR Vari-focal Dome WizMind Network Camera</p> <ul style="list-style-type: none"> . 8 MP 1/1.8" CMOS image sensor, low luminance, and high definition image . Outputs max. 8MP (3840× 2160) @30 fps, Max. IR distance: 80 m . ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments . Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes . Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card . 24V AC/PoE/12V DC power supply . ePoE, IP67, IK10 protection, SMD 3.0 		<p>۲۸۴,۸۵۶,۰۰۰ ریال</p>
24	<p>DH-IPC-HDBW5831RP-ZE</p> 	<p>8MP WDR IR Dome Network Camera</p> <ul style="list-style-type: none"> > 1/2.5" 8Megapixel progressive scan STARVIS™ CMOS > H.265&H.264 dual-stream encoding > 15fps@4K(3840x2160),25/30fps@3M(2304x1296) > Day/Night(ICR), 3DNR, AWB, AGC, BLC > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS > 2.7mm ~12mm motorized lens > Max. IR LEDs Length 50m > Micro SD card memory, IP67,IK10, PoE 		<p>۱۸۵,۹۶۰,۰۰۰ ریال</p>

25	<p>DH-IPC-HDBW5541EP-ZE</p> 	<ul style="list-style-type: none"> · 1/2.7" 5Megapixel progressive scan CMOS · H.265&H.264 triple-stream encoding · 20fps@2592×1944 · WDR(120dB), Day/Night(ICR), 3D DNR, AWB, AGC, BLC · 2.7mm ~13.5mm motorized lens · 1/1 Alarm in/out, 1/1 audio in/out · Max. IR LEDs Length 40m · Micro SD memory, IP67, IK10      	 <p>ریال ۲۱۲,۲۰۰,۰۰۰</p>
26	<p>DH-IPC-HDBW5442EP-ZE</p> 	<ul style="list-style-type: none"> · 4MP IR Vari-focal Dome WizMind Network Camera · 1/1.8" 4Megapixel progressive scan CMOS · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · 25/30 fps@2688 × 1520, 50/60 fps@1080P (1920 × 1080) · WDR (140 dB), Day/Night (ICR), 3D DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS · 2.7 mm~12.0 mm motorized lens . 1/1 Alarm in/out, 1/1 audio in/out · Max. IR LEDs Length 40 m . Micro SD memory, IP67, IK10      	 <p>ریال ۲۳۴,۹۷۲,۰۰۰</p>
27	<p>DH-IPC-HDW5541TMP-ASE</p> 	<ul style="list-style-type: none"> · 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. · Outputs max. 5 MP (2960 × 1668) @25/30fps. · Built-in IR LED, and the max. illumination distance is 50 m. · ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments. · Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. · With deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting, etc. · Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 512 GB Micro SD card, built-in MIC. · 12 VDC/PoE power supply; ePoE. · IP67 protection. · SMD 3.0.      	 <p>ریال ۱۲۶,۸۲۰,۰۰۰</p>
28	<p>DH-IPC-HDW5431RP-ZE</p>  	<ul style="list-style-type: none"> · 1/3" 4Megapixel progressive scan CMOS · H.265&H.264 triple-stream encoding · 25/30fps@4Mp(2688×1520) · Built-in Mic · WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC · Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS · 2.7mm ~13.5mm motorized lens· Max. IR LEDs Length 50m · Micro SD card memory, IP67, PoE     	 <p>#N/A</p>
29	<p>DH-IPC-HDBW3441RP-ZS</p>	<ul style="list-style-type: none"> · 4MP IR Vari-focal Dome WizSense Network Camera · 4MP, 1/3" CMOS image sensor, low illumination, high image definition · Outputs max. 4MP (2688 × 1520)@30 fps · H.265 codec, high compression rate, low bit rate · Built-in IR LED, max. IR distance: 40 m · ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments · Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes · Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human) · Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection · Supports max. 256 G Micro SD card · 12V DC/POE power supply · IP67, IK10 protection, SMD Plus      	 <p>ریال ۱۲۱,۸۶۰,۰۰۰</p>

30 DH-IPC-HDW3449TMP-AS-LED

- 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 4MP (2688 × 1520) @ 30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in Warm LED, max. LEDs distance: 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Supports max. 256 G Micro SD card, built-in Mic
- 12V DC/PoE power support
- IP67 protection · SMD Plus



۸۶,۶۷۰,۰۰۰ ریال

31 DH-IPC-HDBW3441EP-AS

- 4MP IR Fixed focal Dome WizSense Network Camera, **STARLIGHT**
- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- Outputs max. 4MP (2688 × 1520)@30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in IR LED, max. IR distance: 50 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, audio abnormality detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Alarm: In, out; Audio: In, out; Supports max. 256 G Micro SD card
- 12V DC/POE power supply
- IP67, IK10 protection, SMD Plus



۷۱,۸۰۰,۰۰۰ ریال

32 DH-IPC-HDBW3441EP-S

- 4MP IR Fixed focal Dome WizSense Network Camera
- 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- Outputs max. 4MP (2688 × 1520)@30 fps
- H.265 codec, high compression rate, low bit rate
- Built-in IR LED, max. IR distance: 50 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- Supports max. 256 G Micro SD card
- 12V DC/POE power supply
- IP67, IK10 protection, SMD Plus



۶۲,۷۸۰,۰۰۰ ریال

33 DH-IPC-HDBW2831RP-ZS

- 1/1.8" 8Megapixel progressive CMOS
- H.265 & H.264 dual-stream encoding
- 25/30fps@8MP(3840×2160)
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- Micro SD card slot, up to 128GB · IP67, IK10, PoE
- 3.7~11mm motorized lens · Max IR LEDs Length 30m



۱۵۵,۰۶۲,۵۰۰ ریال

34 DH-IPC-HDBW2531RP-ZS

- . 5MP WDR IR Dome Network Camera P6730m
- . 1/2.7" 5Megapixel progressive CMOS
- . H.265 & H.264 dual-stream encoding
- . 15fps@5M(2592×1944)&25/30fps@3M(2304×1296)
- . WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- . Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- . Micro SD card slot, up to 128GB
- . 2.7~13.5mm motorized lens
- . Max IR LEDs Length 30m, IP67, IK10, PoE









۱۵,۴۳۰,۰۰۰ ریال

35 DH-IPC-HDBW2431RP-ZS

- . 1/3" 4MP WDR IR Dome Network Camera
- . H.265 & H.264 dual-stream encoding
- . 20fps@4M(2688×1520)&25/30fps@3M(2304×1296)
- . WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- . Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- . Micro SD card slot, up to 128GB
- . 2.7~13.5mm motorized lens
- . Max IR LEDs Length 30m · IP67, IK10, PoE









۸,۴۰۰,۰۰۰ ریال

36 DH-IPC-HDBW2531EP-S

- . 5MP Lite IR Fixed-focal Dome Network Camera, **STARLIGHT**
- . 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- . Outputs max. 5MP (2592 × 1944) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps
- . H.265 codec, high compression rate, ultra-low bit rate
- . Built-in IR LED, max IR distance: 30 m
- . ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- . Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- . Intelligent detection: Intrusion, tripwire
- . Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection
- . Supports max. 256 GB Micro SD card
- . 12V DC/PoE power supply
- . IP67, IK10 protection










۷,۵۱۰,۰۰۰ ریال

37 DH-IPC-HDW2439TP-AS-LED

- . 4MP Lite Full-color Fixed-focal Eyeball Network Camera
- . 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- . Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps
- . H.265 codec, high compression rate, ultra-low bit rate
- . Built-in warm lights, max. illumination distance: 30 m
- . ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- . Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- . Intelligent detection: Intrusion, tripwire
- . Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- . Supports max. 256 GB Micro SD card and built-in Mic
- . 12V DC/PoE power supply, IP67 protection









۶۷,۳۰۰,۰۰۰ ریال

- 38 DH-IPC-HDBW2431EP-S
- 4MP, 1/3" CMOS image sensor, low illumination, Starlight
 - Outputs 4MP (2560 × 1440)@25/30 fps, max. supports 4MP
 - H.265 codec, high compression rate, ultra-low bit rate
 - Built-in IR LED, max IR distance: 30 m
 - ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
 - Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
 - Intelligent detection: Intrusion, tripwire
 - Abnormality detection: Motion detection, video tampering, no SD
 - Supports max. 256 GB Micro SD card
 - 12V DC/PoE power support · IP67, IK10 protection grade



۵۵,۱۲۰,۰۰۰ ریال

- 39 DH-IPC-HDBW1431EP
- 1/3" 4Megapixel progressive CMOS
 - H.265 & H.264 dual-stream encoding
 - 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296)
 - WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
 - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
 - 2.8 mm fixed lens (3.6 mm optional)
 - Max IR LEDs Length 30m· IP67, IK10, PoE



۲۲,۵۶۰,۰۰۰ ریال

- 40 DH-IPC-HDBW2231RP-ZS
- 2MP WDR IR Dome Network Camera
 - 1/2.8" 2Megapixel progressive StarvisTM CMOS
 - H.265 & H.264 dual-stream encoding
 - 25/30fps@1080P(1920×1080)
 - WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
 - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
 - Micro SD card slot, up to 128GB
 - 2.7~13.5mm varifocal lens
 - Max IR LEDs Length 30m
 - IP67, IK10, PoE



۲۹,۵۷۰,۰۰۰ ریال

- 41 DH-IPC-HDW1431T1P
- 4MP, 1/3" CMOS image sensor, low illumination, high image definition
 - Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520) @20 fps
 - H.265 codec, high compression rate, ultra-low bit rate
 - Built-in IR LED, max. IR distance: 30 m
 - ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
 - Image flip, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
 - Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access, voltage detection
 - 12V DC/PoE power support
 - IP67, protection



۴۵,۵۰۰,۰۰۰ ریال

- 42 DH-IPC-HDW2231TP-AS
- 2MP, 1/2.8" CMOS image sensor, low illumination, high image definition
 - Outputs max. 2MP (1920 × 1080) @25/30 fps
 - H.265 codec, high compression rate, ultra-low bit rate
 - Built-in IR LED, max. IR distance: 30 m
 - ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
 - Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
 - Intelligent detection: Intrusion, tripwire
 - Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
 - Supports max. 256 GB Micro SD card, built-in Mic
 - 12V DC/PoE power supply
 - IP67 protection



۱,۷۳۰,۰۰۰ ریال



43

DH-IPC-HDBW1230EP

- . 1/2.7" 2Megapixel progressive CMOS
- . H.265 & H.264 dual-stream encoding
- . 25/30fps@1080P(1920x1080)
- . DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- . Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- . 2.8mm fixed lens (3.6mm optional)
- . Max IR LEDs length 30m . IP67, IK10, PoE



۳۸,۴۶۰,۰۰۰ ریال

44

DH-IPC-HDW1230T1P

- . 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- . Outputs max. 2MP (1920 × 1080p) @25/30 fps
- . H.265 codec, high compression rate, ultra-low bit rate
- . Built-in IR LED, max. IR distance: 30 m
- . ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- . Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- . Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access
- . 12V DC/PoE power support
- . IP67 protection



۳۵,۳۵۶,۸۰۰ ریال



45

DH-IPC-HDW1239T1P-LED

- . 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- . Outputs max. 2MP (1920 × 1080) @25/30 fps
- . H.265 codec, high compression rate, ultra-low bit rate
- . Built-in LEDs, max LED distance: 15 m
- . ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- . Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- . Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access
- . 12V DC/PoE power support
- . IP67 protection



۳۸,۴۶۰,۰۰۰ ریال



46

DH-IPC-HFW2439SP-SA-LED

- . 4MP Lite Full-color Fixed-focal Bullet Network Camera
- . 4MP, 1/3" CMOS image sensor, low illuminance, high image definition
- . Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps
- . H.265 codec, high compression rate, ultra-low bit rate
- . Built-in warm lights, max. illumination distance: 30 m
- . ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- . Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- . Intelligent detection: Intrusion, tripwire
- . Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection
- . Supports max. 256 GB Micro SD card and built-in Mic
- . > 12V DC/PoE power supply
- . > IP67 protection



۶۷,۴۸۰,۰۰۰ ریال



47 DH-IPC-HFW1239S1P-LED

- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 2MP (1920 × 1080) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in LEDs, max LED distance: 15 m
- ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access
- 12V DC/PoE power support
- IP67 protection



۳۷,۰۹۶,۰۰۰ ریال

48 DH-IPC-HFW1230S1P

- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 2MP (1920 × 1080) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED, max. IR distance: 30 m
- ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access
- 12V DC/PoE power support
- IP67 protection



۳۴,۶۰۰,۰۰۰ ریال

49 DH-SD5A245GB-HNR

- > 1/2.8" 2Megapixel STARVIS™ CMOS.
- > 45x optical zoom.
- > Starlight technology.
- > Max. 25/30fps@1080P.
- > IR distance up to 150 m.
- > Auto-tracking 3.0.
- > Perimeter protection.
- > Face detection.
- > SMD 4.0.
- > Quick Pick.
- > IP67, IK10.



۳۳,۰۱۰,۰۰۰ ریال

50 DH-SD5A432XB-HNR

- 1/2.8" 4Megapixel STARVIS™ CMOS
- Powerful 32x optical zoom
- Max. 25/30fps@4M
- IR distance up to 150 m
- Deep-learning-based auto tracking and perimeter protection
- SMD PLUS
- PoE+
- IP67, IK10
- Face Detection



۳۰,۲۲۵,۰۰۰ ریال

51 DH-SD5A432GB-HNR

- > 1/2.8" 4Megapixel STARVIS™ CMOS.
- > Powerful 32x optical zoom.
- > Max. 25/30 fps@4M.
- > IR distance up to 150 m.
- > Auto Tracking 3.0.
- > Face Detection.
- > SMD 4.0.
- > Quick Pick.
- > PoE+.
- > IP67, IK10.



۲۹,۴۹۰,۰۰۰ ریال

52	DH-SD5A232XB-HNR	<p>2MP 32x Starlight IR WizSense Network PTZ Camera</p> <ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32x optical zoom > Max. 50/60 fps@1080P > IR distance up to 150 m > Deep-learning-based auto tracking and perimeter protection > SMD PLUS > PoE+ > IP67, IK10 > Face Detection 		<p>۴۸۹,۶۷۰,۰۰۰ ریال</p>
53	DH-SD59230U-HNI	<p>2MP 32x Starlight IR WizSense Network PTZ Camera</p> <ul style="list-style-type: none"> > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32x optical zoom > Max. 50/60 fps@1080P > IR distance up to 150 m > Deep-learning-based auto tracking and perimeter protection > SMD PLUS > PoE+ > IP67, IK10 > Face Detection 		<p>۵۱۰,۴۰۰,۰۰۰ ریال</p>
54	DH-SD49225XA-HNR	<p>2MP 25x Starlight IR WizSense Network PTZ Camera</p> <ul style="list-style-type: none"> 1/2.8" 2Megapixel CMOS Powerful 25x optical zoom Starlight technology Max. 50/60fps@1080P Perimeter protection . Support PoE+ IR distance up to 100m . SMD PLUS . IP66 		<p>۲۹۱,۳۱۹,۶۰۰ ریال</p>
55	DH-SD29204UE-GN	<ul style="list-style-type: none"> 1/2.8" STARVIS™ CMOS . STARLIGHT Powerful 4x optical zoom Support Triple-streams encoding WDR, Day/Night(ICR), Ultra DNR Max. 25/30fps@1080P · IVS Support PoE · IR distance up to 30m 		<p>۱۴۴,۹۲۰,۰۰۰ ریال</p>
56	DH-NVR1B04 	<p>4 Channel Smart 1U H.265 Network Video Recorder decoding</p> <ul style="list-style-type: none"> Max 4 channel IP camera inputs Max 80Mbps incoming bandwidth Up to 8MP resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output 		<p>۲۸,۲۴۰,۰۰۰ ریال</p>
57	DH-NVR1B04-4P 	<p>4 Channel Smart 1U H.265 Network Video Recorder decoding</p> <ul style="list-style-type: none"> Max 4 channel IP camera inputs Max 80Mbps incoming bandwidth Up to 8MP resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support IPC UPnP, 4PoE ports 1 SATA III Port, up to 6TB capacity for each HDD 		<p>۴۵,۷۲۰,۰۰۰ ریال</p>

58	DH-NVR104-P 	<ul style="list-style-type: none"> . 4CH Smart Box 4PoE Network Video Recorder . Up to 4 channel IP camera input . H.264/MJPEG dual codec decoding . Max 56Mbps incoming bandwidth . HDMI/VGA simultaneous video output . All channel synchronous realtime playback, GRID interface . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 . Support IPC UPnP, 4PoE ports . Support P2P (QR code Scan) 		۴۱۰۳۰۰۰۰ ریال
59	DH-NVR108-P 	<ul style="list-style-type: none"> . 8CH Smart Box 4PoE Network Video Recorder . Up to 8 channel IP camera input . H.264/MJPEG dual codec decoding . Max 56Mbps incoming bandwidth . HDMI/VGA simultaneous video output . All channel synchronous realtime playback, GRID interface . Support 1 SATA (2.5"removable HDD) up to 1TB, 2 USB2.0 . Support IPC UPnP, 4PoE ports . Support P2P (QR code Scan) 		۴۷۰۸۲۰۰۰۰ ریال
60	DH-NVR608-64-4KS2	<ul style="list-style-type: none"> . Intel Quad-core Processor . 64 channel IPC input-32 Channel Live Preview: (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) . H.265/H.264/MJPEG codec decoding . Max 384Mbps incoming bandwidth . 2HDMI/VGA simultaneous video output . Up to 12Mp resolution preview & playback . RS232 , RS485-16 Alarm In . Support 8 SATA HDDs up to 64TB,1 eSATA Port . Support Raid 0/1/5/6/10 . Support Smart Tracking and Intelligent Video . 4 USB(2 USB3.0, 2 USB2.0)-2*1000 Mbps Network Card 		۹۰۸۰۸۰۰۰۰ ریال
61	DH-NVR608H-32-XI	<ul style="list-style-type: none"> . 32 Channels 2U 8HDDs WizMind Network Video Recorder > 32-channel 1080p self-adaptive decoding capability. > Max. 1024/1024/800Mbps incoming/recording/outgoing bandwidth. > Supports N+M cluster. > Support Raid0/1/5/6/10. > Drawer-like chassis design allows for HDD hot swapping. > AI by recorder: 4-channel face detection and recognition; 8-channel metadata; 24-channel perimeter protection; 32-channel SMD Plus. > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting. 		۱۰۶۱۰۸۰۰۰۰ ریال
62	DH-NVR608-32-4KS2	<ul style="list-style-type: none"> . Intel Dual-core Processor-32 channel IPC input . 32 Channel Live Preview: 16 Alarm In , 8 Relay Output . (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) . H.265/H.264/MJPEG codec decoding . Max 384Mbps incoming bandwidth . Up to 12Mp resolution preview&playback . 2HDMI/VGA simultaneous video output . Support 8 SATA HDDs up to 64TB,1 eSATA Port . Support Raid 0/1/5/6/10-4 USB(2 USB3.0, 2 USB2.0) . 2*1000 Mbps Network Card-RS232 , RS485 		۵۰۲۰۹۵۷۰۰۰ ریال

63

DH-NVR5864-EI

64 Channels 2U 8HDD WizSense Network Video Recorder

- > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.
- > 32-channel 1080p self-adaptive decoding capability.
- > Support Raid0/1/5/6/10.
- > Max. 384 Mbps incoming/recording/outgoing bandwidth.
- > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.
- > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.
- > Security baseline 2.3.



۳۹,۷۰۰,۰۰۰ ریال

64

DH-NVR5832-EI

32 Channels 2U 8HDD WizSense Network Video Recorder

- > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.
- > 32-channel 1080p self-adaptive decoding capability.
- > Max. 384 Mbps incoming/recording/outgoing bandwidth.
- > Support Raid0/1/5/6/10.
- > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.
- > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.
- > Security baseline 2.3.



۵۶,۷۰۰,۰۰۰ ریال

65

DH-NVR5832-4KS2

- . 32 channel IPC input-32 Channel Live Preview
- . H.265/H.264/MJPEG/MPEG4 codec decoding
- . Max 320Mbps incoming bandwidth . P2P Support-Raid 0/1/5/6/10
- . Up to 12MP resolution preview&playback
- . Max 16ch@1080P | 4ch@4K H.265 | H.264 Playback
- . 2HDMI/VGA simultaneous video output
- . Support 8 SATA HDDs up to 64TB, 4 USB(2 USB3.0, 2 USB2.0)
- . 2*1000 Mbps Network Card-RS232-16 Alarm In , 6 Relay Output



۴۴۷,۸۷۶,۰۰۰ ریال

66

DH-NVR5432-16P-4KS2E

- . 32Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder
- . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- . Max 320Mbps Incoming Bandwidth
- . Up to 12MP Resolution for Preview and Playback
- . 2HDMI/VGA simultaneous video output
- . 3D intelligent positioning with Dahua PTZ camera
- . 4 SATA III Ports, Up to 8 TB capacity for each HDD



۴۶۱,۲۳۰,۰۰۰ ریال

67

DH-NVR5432-EI

32 Channels 1.5U 4HDD WizSense Network Video Recorder

- > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.
- > 32-channel 1080p self-adaptive decoding capability.
- > Max. 384 Mbps incoming/recording/outgoing bandwidth.
- > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.
- > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.
- > Security baseline 2.3.



ریال ۳۹۳,۱۹۰,۰۰۰

68

DH-NVR5432-4KS2

32 Channel 1.5U 16PoE 4K&H.265 Pro Network Video Recorder

- Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- Max 320Mbps Incoming Bandwidth
- Up to 12MP Resolution for Preview and Playback
- 2HDMI/2VGA simultaneous video output
- 1-8 PoE Ports Support 800m ePoE & EoC



ریال ۳۱۳,۳۷۵,۰۰۰

69

DH-NVR5232-EI

32 Channels 1U 2HDD WizSense Network Video Recorder

- > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.
- > 32-channel 1080p self-adaptive decoding capability.
- > Max. 384 Mbps incoming/recording/outgoing bandwidth.
- > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.
- > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.
- > Security baseline 2.3.



ریال ۲۷۵,۵۹۰,۰۰۰

70

DH-NVR5232-4KS2

- 32 channel IP camera input. 32 channel Live Preview
- Up to 12Mp resolution preview&playback
- Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- Max 320Mbps incoming bandwidth-Record Rate 320 Mbps
- Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding
- HDMI/VGA simultaneous video output-16 channel playback
- Support 2 SATA HDDs up to 20TB, 2 USB(1 USB3.0)
- 1000 Mbps Network Card -RS232, RS485
- 4 Alarm Input, 2 Relay Output-Support P2



ریال ۲۴۴,۶۲۲,۴۰۰

71

DH-NVR5216-16P-I

Wiz Mind

- 16Channel 1U 16PoE AI Network Video Recorder
- 16 Channel IP video access
- Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- Up to 16 Channel perimeter protection
- Up to 4 Channel video stream face recognition
- Up to 22 face pictures /sec processing
- Up to 20 face databases with 100,000 face images in total
- 1-8 PoE Ports support ePoE & EoC



ریال ۶۷۰,۰۴۰,۰۰۰

72 DH-NVR5216-16P-4KS2E

- .32 Channel 1U 2HDDs 16PoE 4K & H.265 Pro Network Video Recorder
- .32-channel IP video access
- . Smart H.265+/Smart H.264+/H.264/MJPEG; H.265 auto switch
- . Max 320 Mbps incoming bandwidth
- . Up to 24MP resolution for live view and playback
- . 1-channel fisheye dewarping (AI by NVR)
- . AI by Camera: Perimeter protection; face detection and recognition; SMD Plus; video metadata; ANPR; people counting; stereo analysis; crowd distribution; heat map
- . Support IPC UPnP, 16 PoE ports



۲۸۷,۷۴۱,۵۰۰ ریال

73 DH-NVR5216-EI

- . 16 Channels 1U 2HDD WizSense Network Video Recorder
- > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.
- > 32-channel 1080p self-adaptive decoding capability.
- > Max. 384 Mbps incoming/recording/outgoing bandwidth.
- > AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.
- > AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.
- > Security baseline 2.3



۲۴۵,۰۷۰,۰۰۰ ریال

74 DH-NVR5216-4KS2

- . 16Channel 1U 4K&H.265 Pro Network Video Recorder (V2.00)
- . Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- . Max 320Mbps Incoming Bandwidth
- . Up to 12MP Resolution for Preview and Playback
- . HDMI/VGA simultaneous video output
- . 2 SATA III Ports, Up to 10 TB capacity for each HDD



۲۰۷,۴۶۰,۰۰۰ ریال

75 DH-NVR4432-4KS2

- . 32 channel IP camera input. 1.5U
- . 16 channel Live Preview-H.265/H.264 codec decoding
- . Max 200Mbps incoming bandwidth
- . Up to 8MP Resolution for Preview and Playback
- . HDMI/VGA simultaneous video output
- . Support 4 SATA HDD up to 6TB
- . 2 USB Ports (1 USB2.0, 1 USB3.0)
- . 16 Alarm Input, 4 Relay Output-RS232, RS485
- . 2*10/100/1000Mbps Mbps Network Card-P2P support



۱۹۹,۸۱۰,۰۰۰ ریال

76 DH-NVR4232-4KS2/L

- . New 4.0 user interface, Security baseline 2.1
- . H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch
- . Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding
- . Supports mainstream cameras of ONVIF and RTSP protocols
- . P2P remote surveillance, video play on mobile device
- . VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- . AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD
- . Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches



۴۰۶,۰۰۰ ریال

77	DH-NVR4232-4KS2	<ul style="list-style-type: none"> 32-channel IP video access Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch Max 200 Mbps incoming bandwidth Up to 8MP resolution for preview and playback 8-channel decoding@1080p (30 fps) AI by Camera: Perimeter protection; SMD Plus; people counting; heat map 	
----	-----------------	--	---



۱۴۳,۳۹۰,۰۰۰ ریال

78	DH-NVR4216-16P-4KS2/L	<p>16 Channel 1U 2HDDs 16PoE Network Video Recorder- New 4.0 user interface, Security baseline 2.1</p> <ul style="list-style-type: none"> H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	
----	-----------------------	--	---



۱۴۳,۱۷۷,۰۰۰ ریال

79	DH-NVR4216-4KS2/L	<p>16 Channel 1U 2HDDs Network Video Recorder</p> <ul style="list-style-type: none"> New 4.0 user interface, Security baseline 2.1 H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	
----	-------------------	--	---



۱۴۳,۰۲۲,۰۰۰ ریال

80	DH-NVR4116HS-4KS2/L	<ul style="list-style-type: none"> New 4.0 user interface, Security baseline 2.1 H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding Supports mainstream cameras of ONVIF and RTSP protocols P2P remote surveillance, video play on mobile device VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	
----	---------------------	--	---



۹۴,۰۹۰,۰۰۰ ریال

81	DH-NVR4108HS-8P-4KS2/L	<ul style="list-style-type: none"> · New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch · Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding · Supports mainstream cameras of ONVIF and RTSP protocols · P2P remote surveillance, video play on mobile device · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K · AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD · Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	 ۵۱.۷۶۷,۰۰۰ ریال
82	DH-NVR4108HS-4KS2	<p>8 Channel Compact 1U 4K&H.265 Lite Network Video Recorder</p> <ul style="list-style-type: none"> · Smart H.265+/H.265/Smart H.264+/H.264 · Max 80Mbps Incoming Bandwidth · Up to 8MP Resolution for Preview and Playback · Up to 2ch@4K/8ch@1080P decoding · HDMI/VGA simultaneous video output 	 ۵.۵۲۰,۰۰۰ ریال
83	DH-NVR4108HS-4KS2/L	<ul style="list-style-type: none"> · New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch · Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding · Supports mainstream cameras of ONVIF and RTSP protocols · P2P remote surveillance, video play on mobile device · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K · AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD · Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	 ۶۹.۹۶۰,۰۰۰ ریال
84	DH-NVR4104HS-P-4KS2/L	<p>4 Channel Compact 1U 1HDD 4PoE Network Video Recorder</p> <ul style="list-style-type: none"> · New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch · Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding · Supports mainstream cameras of ONVIF and RTSP protocols · P2P remote surveillance, video play on mobile device · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K · AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD · Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 	 ۸۹.۸۶۸,۸۰۰ ریال

85	DH-NVR4104HS-4KS2/L	<ul style="list-style-type: none"> . 4 Channel Compact 1U 1HDD Network Video Recorder .. New 4.0 user interface, Security baseline 2.1 . H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch . Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding . Supports mainstream cameras of ONVIF and RTSP protocols . P2P remote surveillance, video play on mobile device . VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K . AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SIMD . Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches 		۶۱,۰۴۰,۰۰۰ ریال
86	DH-NVR2108HS-8P-4KS2	<ul style="list-style-type: none"> . 8 Channel Compact 1U 8PoE Lite 4K . H.265/H.264 codec decoding . HDMI/VGA simultaneous video output . Max 80Mbps incoming bandwidth . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . Support 1 SATA HDD up to 6TB, 2 USB2.0 . 100 Mbps Network Card-8Port PoE. P2P support 		۱۰۹,۰۰۰,۰۰۰ ریال
87	DH-NVR2104HS-P-4KS2	<ul style="list-style-type: none"> . 4 Channel Compact 1U 4PoE Lite 4K. H.265/H.264 codec decoding . Max 80Mbps incoming bandwidth-Up to 8Mp resolution . preview&playback-Up to 1ch@8MP/4ch@1080P decoding . HDMI/VGA simultaneous video output . Support 1 SATA HDD up to 6TB, 2 USB2.0 . 100 Mbps Network Card-4PoE Port. P2P support 		۷۶,۹۴۰,۰۰۰ ریال
88	DH-NVR2108HS-4KS2	<ul style="list-style-type: none"> . 8 channel IP camera input 1U Lite 4K . H.265/H.264 codec decoding . 100 Mbps Network Card. P2P support . Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . Support 1 SATA HDD up to 6TB, 2 USB2.0 		۵۶,۴۲۰,۰۰۰ ریال
89	DH-NVR2104HS-4KS2	<ul style="list-style-type: none"> . 4 channel IP camera input 1U Lite 4K . H.265/H.264 codec decoding . 100 Mbps Network Card. P2P support . Max 80Mbps incoming bandwidth . HDMI/VGA simultaneous video output . Up to 8Mp resolution preview&playback . Up to 1ch@8MP/4ch@1080P decoding . Support 1 SATA HDD up to 6TB, 2 USB2.0 		۴۸,۷۳۰,۰۰۰ ریال

90	DH-NVR1108HS-8P-S3/H	<ul style="list-style-type: none"> · New 4.0 user interface · P2P remote surveillance, video play on mobile device · 8-ch@1080P(30FPS), self-adaptive decoding capability · Support for mainstream cameras of ONVIF and RTSP protocol · Smart H.265+/Smart H.264+/H.265/H.264 · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P · Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches · DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain Name System) 		۷۴,۶۳۰,۰۰۰ ریال
91	DH-NVR1104HS-P-S3/H	<ul style="list-style-type: none"> · New 4.0 user interface · P2P remote surveillance, video play on mobile device · 4-ch@1080P(30FPS), self-adaptive decoding capability · Support for mainstream cameras of ONVIF and RTSP protocol · Smart H.265+/Smart H.264+/H.265/H.264 · VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P · Remote configuration and management of IPCs, such as setting parameters, acquiring information and upgrading IPCs of the same model in batches · DHCP(Dynamic Host Configuration Protocol), HTTP(Hypertext Transfer Protocol), NTP(Network Time Protocol) and DDNS(Dynamic Domain Name System) 		۵۲,۵۴۰,۰۰۰ ریال
92	DH-PFS3226-24ET-240	<ul style="list-style-type: none"> > Intelligent PoE > PD Alive(PoE Watchdog) > Long Distance PoE Transmission > Smooth Transmission > Wide Working Temperature: -10 to 55°C (14°F to 131°F) > Port Isolation 		۱۹۷,۳۶۰,۰۰۰ ریال
93	DH-PFS3218-16ET-135	<ul style="list-style-type: none"> > Intelligent PoE > PD Alive(PoE Watchdog) \ > Long Distance PoE Transmission > Smooth Transmission > Wide Working Temperature: -10 to 55°C (14°F to 131°F) > Port Isolation 		۱۵۰,۹۸۸,۰۰۰ ریال
94	DH-PFS3010-8ET-96	<ul style="list-style-type: none"> · 8-Port PoE Switch (Unmanaged) . Layer two commercial switch · Supports PoE power management · Supports wall-mount installation · Supports anti-theft lock hole · MAC auto learning and aging, MAC address capacity is 16K · Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards · RJ45 port supports 10/100 Mbps self-adaptation · Supports 250 meters long distance PoE transmission · Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply 		۶۴,۹۰۰,۰۰۰ ریال
95	DH-PFS3106-4ET-60	<ul style="list-style-type: none"> · 4-Port PoE Switch (Unmanaged) · Layer two Hardened PoE switch · Supports PoE power management · MAC auto learning and aging, MAC address capacity is 8K · Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply · Supports IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards · Wide working temperature design: -30°C~ 65°C · Supports dual power backup 		۵۷,۷۰۰,۰۰۰ ریال

96	DH-PFS3102-1T	<ul style="list-style-type: none"> 2-layer industrial level Ethernet media converter Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards 100M/1000M self-adaptive SFP fiber port Industrial wide temperature design 		۲۶,۸۹۰,۰۰۰ ریال
97	DH-LR2218-16ET-240	<ul style="list-style-type: none"> 16-Port ePoE Switch Supports long distance PoE transmission up to 800m with ePoE technology of Dahua Layer-two web managed ePoE switch Port 1-8 support three self-adaptive transmission modes which are IEEE, E100 and E10 Port 1-8 support both twisted-pair transmission and coaxial cable transmission Support web management: port management, 802.1Q VLAN, STP/RSTP, LACP, 802.1X, QoS Support PoE management, Green PoE, Legacy Support Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and 		۲۰,۵۲۱۰,۰۰۰ ریال
98	DH-LR2110-8ET-120	<ul style="list-style-type: none"> 8-Port ePoE Switch Supports long distance PoE transmission up to 800m with ePoE technology of Dahua Layer-two ePoE switch MAC auto study and aging, MAC address list capacity is 8K Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Supports IEEE802.3af, IEEE802.3at, Hi-PoE standard Industrial wide temperature design Port indicator light is to display the status of current transmission mode for the port, which includes IEEE, E100 and E10 		۱۲۱,۸۳۰,۰۰۰ ریال
99	DH-PFL2106-4ET-96	<ul style="list-style-type: none"> 4-Port ePoE Switch Supports long distance PoE transmission up to 800m with ePoE technology of Dahua Two-layer industrial PoE switch MAC auto study and aging, MAC address list capacity is 8K Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards Supports IEEE802.3af, IEEE802.3at, Hi-PoE standard Industrial wide temperature design 		۸۰,۷۷۰,۰۰۰ ریال
100	DH-NKB1000-E	<p>Keyboard to Control</p> <ul style="list-style-type: none"> Dahua High Speed Dome · Dahua Standalone DVR Network Video Server Connection RS485, RS422 (reserved), USB, RS232 & Network Functions Three Dimensional Joystick Control of PTZ Functions Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions On-Screen Menu & User Operation Procedure Tips Connect to SmartPSS or DSS platform via USB 		۱۶۹,۹۰۰,۰۰۰ ریال
101	DH-PFM900-E	<p>Integrated Mount Tester</p> <ul style="list-style-type: none"> > 4.0" TFT screen, 800 × 480 resolution > H.264/H.265 decoding display for IPC > HDCVI/AHD/TVI/CVBS video display control > Support SD and HD direct switch > 12V/2A DC power supply for the camera > Support RS-485 control, and audio test > Length and attenuation tests of the network cable > Functions of digital multimeter 		۴۸۳,۰۰۰,۰۰۰ ریال